

# KERN CB 1500-3Q2

# KERN

Bending beam and shear beam load cell made from stainless steel



Dimension (Ø×H)	50×136,5 mm
Material	stainless steel
Cable length	3 m
Mounting - force dissipation	2 × through hole Ø 13 mm
Mounting - force application	Through-hole Ø 13 mm

## Functions

IP protection - complete device	IP68
---------------------------------	------

## Environmental conditions

Ambient temperature [Min]	-30 °C
Ambient temperature [Max]	70 °C
Use temperature [Min]	-10 °C
Use temperature [Max]	40 °C

## Approval


CE mark	✓
---------	---

## Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	250×155×60 mm
Net weight	0,454 kg
Shipping method	Parcel service
Net weight approx.	0,50 kg
Gross weight approx.	0,75 kg
Shipping weight	0,714 kg

## Pictograms

### STANDARD



### OPTION



## Category

Brand	Sauter
Product category	Measuring cell
Product group	Load cell
Product family	CB Q2

## Measuring System

Weighing capacity [Max]	1500 kg
Directions of force	compression
Load cell connection	4-wire
Load cell OIML class	C2
Load cell - Resolution (verifiable)	2000 e
Load cell - characteristic value - nominal	2 mV/V
Load cell - characteristic value - variance	0,002 mV/V
Load cell - Y-value	10000
Load cell - Combined error	0,017%
Load cell - Dead load [Min] (%)	0%
Measuring applications	mass
Load cell - Input resistance - nominal	400 Ω
Load cell - Output resistance - nominal	350 Ω
Load cell - Isolation resistance - [Min]	5000 MΩ
Load cell - Recommended excitation voltage [Min]	10 V
Load cell - Recommended excitation voltage [Max]	15 V
Load cell - Input resistance - variance	20 Ω
Load cell - Output resistance - variance	3 Ω

## Construction

Design	bending beam
--------	--------------