SAUTER **CB 1500-3Q2**

Bending beam and shear beam load cell made from stainless steel



Date of creation: 23.10.2026

Category	
Brand	Sauter
Product category	Measuring cell
Product group	Load cell
Product family	CB Q2

Measuring System	
Weighing capacity [Max]	1500 kg
Load cell - characteristic value - nominal	2 mV/V
Load cell - characteristic value - variance	0,002 mV/V
Load cell OIML class	C2
Load cell connection	4-wire
Load cell - Resolution (verifiable)	2000 e
Load cell - Dead load [Min] (%)	0%
Measuring applications	mass
Directions of force	compression
Load cell - Y-value	10000
Load sell - Input resistance - nominal	400 Ω
Load cell - Output resistance - nominal	350 Ω
Load cell - Input resistance - variance	20 Ω
Load cell - Output resistance - variance	3 Ω
Load cell - Recommended exitation voltage [Min]	10 V
Load cell - Recommended exitation voltage [Max]	15 V
Load cell - Isolation resistance - [Min]	5000 MΩ
Load cell - Combined error	0,017%

Functions	
IP protection - complete device	IP68

Construction	
Material	steel, stainless
Design	bending beam
Dimension (Ø×H)	50×136,5 mm
Cable length	3 m
Mounting - force application	Through-hole Ø 13 mm
Mounting - force dissipation	2 × through hole Ø 13 mm

Environmental conditions	
Ambient temperature [Min]	-30 °C
Ambient temperature [Max]	70 °C
Use temperature [Min]	-10 °C
Use temperature [Max]	40 °C

Approval	
CE mark	✓

Product information	
GTIN/EAN number	4045761220799
Trade number	84239010
Warranty Time	24 mon
REACH classification	no prohibited substances

Packing & Shipping	
Shipping method	Parcel service
Delivery time	1 d
Dimensions packaging (W×D×H)	250×155×60 mm
Net weight approx.	0,50 kg
Gross weight approx.	0,75 kg
Shipping volume weight	0,5 kg

SAUTER **CB 1500-3Q2**

Bending beam and shear beam load cell made from stainless steel

Pictograms

STANDARD



OPTION

