

# KERN CCS 10K-6

Counting system to count the smallest parts in large quantities, maximum number of parts which can be displayed is 999,999



Display	
Display type	LCD
Display backlight	✓
Display digit height	20 mm

Construction	
Dimensions completely mounted (W×D×H)	320×330×125 mm
Dimensions weighing surface (W×D)	300×240 mm
Dimensions weighing surface	300×240 mm
Dimensions weighing platform (W×D×H)	300×240×105 mm
Material housing	plastic
Material weighing plate	stainless steel
Material load cell(s)	aluminium
Level indicator	✓
Levelling feet adjustable	✓
Cable length	1,5 m
Display device cable length	3 m

Functions	
PreTare function	✓
Sum memory function	✓
Recipe/summing level	Sum A
Conversion function	✓
PLU - total	100
Tolerance weighing	✓
Counting function	✓
Counting resolution (laboratory conditions)	3.000.000
Counting reference weight can be entered	✓
Smallest piece weight when piece counting - laboratory conditions	5 mg
Smallest piece weight when piece counting - normal conditions	50 mg
Reference quantity	n (any number of pieces)
IP protection - display	IP23
IP protection - platform	IP65
IP protection - load cell	IP65
Memory function	✓
Auto-off interval(s) in battery mode/rechargeable battery mode	selectable
Auto-off interval(s) in mains power mode	5 min 30 min 15 min
Tare function	manual (multi)

Category	
Brand	KERN
Product category	Industrial scale
Product group	Counting system
Product family	CCS

Measuring System	
Reference scale - item number	CFS 300-3
Quantity scale - Item number	KFP 15V20M
Construction type of the scale	Multi-range balance
Weighing system	Strain gauge
Reference scale - Weighing capacity [Max]	0,3 kg
Quantity scale - Weighing capacity [Max]	15 kg
Quantity scale - Readability [d]	0,0005 kg
Reference scale - Readability [d]	1 mg
Reproducibility	0,000002 kg
Reference scale - Reproducibility	2 mg
Quantity scale - Reproducibility	0,0005 kg
Linearity	±
Reference scale - Linearity	4 mg
Quantity scale - Linearity	0,0015 kg
Adjustment options	Adjusting with external weight
Recommended adjusting weight	15 kg (F 1)
Stabilization time	2 s
Warm-up time	120 min
Eccentric loading at 1/3 [Max]	0,000006 kg
Reference scale - Eccentric loading at 1/3 [Max]	6 mg
Quantity scale - Eccentric loading at 1/3 [Max]	0,0025 kg
Default unit	kg
Units	g lb
Loadcell type	aluminum Alloy IP64

# KERN CCS 10K-6

# KERN

Counting system to count the smallest parts in large quantities, maximum number of parts which can be displayed is 999,999

## Interface

Interfaces	RS-232 standard
------------	-----------------

## Power Supply

Supplied power supply	Power supply unit
-----------------------	-------------------

Plug-in power supply type	Power adapter
---------------------------	---------------

Plug-in power supply / adapter for countries - included with the delivery	EURO
	UK
	US
	CH

Plug-in power supply / adapter for countries - optional	EURO
	UK
	US
	CH

Input voltage power supply / power [Max]	220 V - 240 V AC, 50 Hz
--	-------------------------

Input voltage device / power [Max]	12 V, 500 mA
------------------------------------	--------------

Battery / accumulator type	Pb
----------------------------	----

Rechargeable battery	GAB-A04
----------------------	---------

Rechargeable battery operating time - backlight on	40 h
--	------

Rechargeable battery operating time - backlight off	60 h
---	------

Rechargeable battery charging time	12 h
------------------------------------	------

Rechargeable battery optional	Rchrg. battery optional
-------------------------------	-------------------------

## Environmental conditions

Ambient temperature [Min]	0 °C
---------------------------	------

Ambient temperature [Max]	40 °C
---------------------------	-------

Humidity of environment [Min]	0 %
-------------------------------	-----

Humidity of environment [Max]	80 %
-------------------------------	------

Storage temperature [Min]	-20 °C
---------------------------	--------

Storage temperature [Max]	60 °C
---------------------------	-------

## Approval

CE mark	✓
---------	---

## Services (optional)

Article number for adjustment at the location of installation	abhängig von Auflösung/ Max   depends on resolution and capacity
---	--

Article number for DAkKS calibration	962-128-127
--------------------------------------	-------------

Article number for certificate of conformity	969-517
--	---------

## Packing & Shipping

Delivery time	2 d
---------------	-----

Dimensions packaging (W×D×H)	630×535×350 mm
------------------------------	----------------

Shipping method	Parcel service
-----------------	----------------

Net weight approx.	7 kg
--------------------	------

Gross weight approx.	10 kg
----------------------	-------

Shipping weight	23,6 kg
-----------------	---------

## Pictograms

### STANDARD



### OPTION

