SAUTER CS 200-3Q1



6-wire "S" measuring cell made of nickel-plated steel for force and mass measurement



Category	
Brand	Sauter
Product categoriy	Measuring cell
Product group	Load/force measuring cell
Product family	CS Q1

Measuring System	
Weighing capacity [Max]	200 kg
Load cell connection	6-wire
Measuring range force [Max] (N)	2 kN
Load cell - Input resistance - variance	20 Ω
Load cell - Resolution (verifiable)	3000 e
Load cell - Output resistance - variance	3 Ω
Load cell OIML class	C3
Directions of force	tension compression
Load cell - characteristic value - nominal	2 mV/V
Load cell - characteristic value - variance	0,002 mV/V
Load cell - Y-value	10000
Load cell - Combined error	0,017%
Load cell - Dead load [Min] (%)	0%
Measuring applications	force mass
Load sell - Input resistance - nominal	400 Ω
Load cell - Output resistance - nominal	350 Ω

Load cell - Isolation resistance - [Min]	5000 ΜΩ
Load cell - Recommended exitation voltage [Min]	10 V
Load cell - Recommended exitation voltage [Max]	15 V

Load cell - Recommended exitation voltage [Max]	15 V	
Construction		
Design	"S" shaped cell	
Dimension (W×D×H)	80×62,1×19 mm	
Material	steel, nickel-plated	
Cable length	5 m	
Mounting - force dissipation	Threaded hole M12	
Mounting - force application	Threaded hole M12	
Functions		
IP protection - complete device	IP67	
Environmental conditions		
Ambient temperature [Min]	-10 °C	
Ambient temperature [Max]	40 °C	
Storage temperature [Min]	-30 °C	
Storage temperature [Max]	70 °C	
Approval		
CE mark	✓	
CE mark Services (optional)	✓	
	963-162V	
Services (optional) Article number for DAkkS		
Services (optional) Article number for DAkkS calibration (tensile force) Article number for DAkkS	963-162V	
Services (optional) Article number for DAkkS calibration (tensile force) Article number for DAkkS calibration (compressive force) Article number for DAkkS calibration (tensile force/	963-162V 963-262V	
Services (optional) Article number for DAkkS calibration (tensile force) Article number for DAkkS calibration (compressive force) Article number for DAkkS calibration (tensile force/ compressive force)	963-162V 963-262V	
Services (optional) Article number for DAkkS calibration (tensile force) Article number for DAkkS calibration (compressive force) Article number for DAkkS calibration (tensile force/ compressive force) Packing & Shipping	963-162V 963-262V 963-362V	
Services (optional) Article number for DAkkS calibration (tensile force) Article number for DAkkS calibration (compressive force) Article number for DAkkS calibration (tensile force/ compressive force) Packing & Shipping Delivery time	963-162V 963-262V 963-362V	
Services (optional) Article number for DAkkS calibration (tensile force) Article number for DAkkS calibration (compressive force) Article number for DAkkS calibration (tensile force/ compressive force) Packing & Shipping Delivery time Dimensions packaging (W×D×H)	963-162V 963-262V 963-362V 1 d 250×155×60 mm	
Services (optional) Article number for DAkkS calibration (tensile force) Article number for DAkkS calibration (compressive force) Article number for DAkkS calibration (tensile force/ compressive force) Packing & Shipping Delivery time Dimensions packaging (W×D×H) Shipping method Net weight approx. Gross weight approx.	963-162V 963-262V 963-362V 1 d 250×155×60 mm Parcel service	
Services (optional) Article number for DAkkS calibration (tensile force) Article number for DAkkS calibration (compressive force) Article number for DAkkS calibration (tensile force/ compressive force) Packing & Shipping Delivery time Dimensions packaging (W×D×H) Shipping method Net weight approx.	963-162V 963-262V 963-362V 1 d 250×155×60 mm Parcel service 0,80 kg	
Services (optional) Article number for DAkkS calibration (tensile force) Article number for DAkkS calibration (compressive force) Article number for DAkkS calibration (tensile force/ compressive force) Packing & Shipping Delivery time Dimensions packaging (W×D×H) Shipping method Net weight approx. Gross weight approx.	963-162V 963-262V 963-362V 1 d 250×155×60 mm Parcel service 0,80 kg 0,90 kg	
Services (optional) Article number for DAkkS calibration (tensile force) Article number for DAkkS calibration (compressive force) Article number for DAkkS calibration (tensile force/ compressive force) Packing & Shipping Delivery time Dimensions packaging (W×D×H) Shipping method Net weight approx. Gross weight approx. Shipping weight	963-162V 963-262V 963-362V 1 d 250×155×60 mm Parcel service 0,80 kg 0,90 kg	

REACH classification

no prohibited substances

SAUTER CS 200-3Q1



6-wire "S" measuring cell made of nickel-plated steel for force and mass measurement

Pictograms		
STANDARD		
1 DAY		
OPTION		
DAKKS SO +4 DAYS		