


# KERN CS 30000-3P1

# KERN

4-wire "S" measuring cell made of nickel-plated steel for force and mass measurement



Load cell - Recommended excitation voltage [Max]	12 V
Load cell - Input resistance - variance	3,5 Ω
Load cell - Output resistance - variance	2 Ω

## Construction

Design	"S" shaped cell
Dimension (W×D×H)	190×230×80 mm
Material	steel, nickel-plated
Cable length	6 m
Mounting - force dissipation	Threaded hole M42 × 3
Mounting - force application	Threaded hole M42 × 3

## Functions

IP protection - complete device	IP67
---------------------------------	------

## Environmental conditions

Ambient temperature [Min]	-35 °C
Ambient temperature [Max]	65 °C
Use temperature [Min]	-10 °C
Use temperature [Max]	40 °C
Storage temperature [Min]	-40 °C
Storage temperature [Max]	70 °C

## Approval

CE mark	✓
---------	---

## Packing & Shipping

Delivery time	113 d
Dimensions packaging (W×D×H)	600×600×200 mm
Net weight	12 kg
Shipping method	Parcel service
Net weight approx.	12 kg
Gross weight approx.	13 kg
Shipping weight	14,4 kg

## Pictograms

STANDARD



## Category

Brand	Sauter
Product category	Measuring cell
Product group	Load/force measuring cell
Product family	CS P1

## Measuring System

Weighing capacity [Max]	30000 kg
Measuring range force [Max] (N)	300 kN
Directions of force	tension compression
Load cell connection	4-wire
Load cell OIML class	C3
Load cell - Resolution (verifiable)	3000 e
Load cell - characteristic value - nominal	2 mV/V
Load cell - characteristic value - variance	0,004 mV/V
Load cell - Y-value	10000
Load cell - Combined error	0,02%
Load cell - Dead load [Min] (%)	0%
Measuring applications	force mass
Load cell - Input resistance - nominal	350 Ω
Load cell - Output resistance - nominal	351 Ω
Load cell - Isolation resistance - [Min]	500 MΩ
Load cell - Recommended excitation voltage [Min]	5 V