

KERN CT 3000-3Q1

KERN

Shear beam made from stainless steel



Dimension (W×D×H)	171,5×48×41,5 mm
Material	stainless steel
Cable length	5 m
Mounting - force dissipation	2 × through hole Ø 20,5 mm
Mounting - force application	Through-hole Ø 20,5 mm

Functions

IP protection - complete device	IP68 IP69K
---------------------------------	---------------

Environmental conditions

Ambient temperature [Min]	-30 °C
Ambient temperature [Max]	70 °C
Use temperature [Min]	-10 °C
Use temperature [Max]	40 °C

Approval

CE mark	✓
---------	---

Services (optional)

Article number for factory calibration (compressive force)	961-265V
--	----------

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	285×115×85 mm
Net weight	2,2 kg
Shipping method	Parcel service
Net weight approx.	2,2 kg
Gross weight approx.	2,4 kg
Shipping weight	2,334 kg

Pictograms

STANDARD



OPTION



Category

Brand	Sauter
Product category	Measuring cell
Product group	Load cell
Product family	CT Q1

Measuring System

Weighing capacity [Max]	3000 kg
Directions of force	compression
Load cell connection	6-wire
Load cell OIML class	C3
Load cell - Resolution (verifiable)	3000 e
Load cell - characteristic value - nominal	2 mV/V
Load cell - characteristic value - variance	0,001 mV/V
Load cell - Y-value	10000
Load cell - Combined error	0,017%
Load cell - Dead load [Min] (%)	0%
Measuring applications	mass
Load cell - Input resistance - nominal	400 Ω
Load cell - Output resistance - nominal	350 Ω
Load cell - Isolation resistance - [Min]	5000 MΩ
Load cell - Recommended excitation voltage [Min]	10 V
Load cell - Recommended excitation voltage [Max]	15 V
Load cell - Input resistance - variance	20 Ω
Load cell - Output resistance - variance	3 Ω

Construction

Design	Shear beam measuring cell
--------	---------------------------