SAUTER **DA 1-4**

Comfortable testing of screw tops, e.g. bottles, jars etc.



Date of creation: 24.10.2026

Category	
Brand	Sauter
Product category	Torque measuring device
Product group	Torquemeter for Twist Locks
Product family	DA

Measuring System	
Test object diameter [Max]	16 cm
Measuring range torque [Max]	1 Nm
Readability torque [d] (Nm)	0,2 mNm
Internal data memory: Number of value groups	1
Overload protection (% of [Max])	120%
Units	Nm, kgf/cm, kgf/m, in/lbs, ft/lbs
Internal measuring frequency	1000 Hz
Tolerance (% of [Max])	0,5%
Internal data memory: Number of individual values	500
Measuring range torque [Min]	0,05 Nm

Display	
Display type	LCD graphic
Display resolution	128×64

Construction	
Dimension (W×D×H)	100×160×250 mm
Dimension housing (W×D×H)	260×160×60 mm
Material housing	metal, lacquered

Functions	
Peak function	✓
Auto-off interval(s) in battery mode/rechargeable battery mode	1 - 60 min
Memory function	✓
Limit-setting function	✓

Interface	
Interfaces	RS-232 standard USB-Device

Power Supply	
Supplied power supply	Accu & Power supply
Power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO CH
Plug-in power supply / adapter for countries - optional	EURO AUS UK US CH
Input voltage power supply / power [Max]	100 V - 240 V
Input voltage device / power [Max]	9 V, 500 mA
Power socket for mains adapter	Hollow plug, inside plus, Ø outside 5,5 mm, Ø inside 2,1 mm, long 10,8 mm
Battery / accumulator type	NiMH
Battery connection	2-pole tub connector
Battery capacity	750 mAh
Battery voltage	4,8 V
Battery – Individual weight	50 g
Rechargeable battery operating time - backlight off	18 h
Rechargeable battery charging time	14 h
Battery/Accu connected	fixed electrical connection, not insulated

Environmental conditions	
Ambient temperature [Min]	15 °C
Ambient temperature [Max]	35 °C
Storage temperature [Min]	-10 °C
Storage temperature [Max]	40 °C

SAUTER **DA 1-4**

Comfortable testing of screw tops, e.g. bottles, jars etc.


Services (optional)	
Article number for factory calibration	961-120

Packing & Shipping	
Delivery time	1 d
Dimensions packaging (W×D×H)	370×325×110 mm
Shipping method	Parcel service
Net weight approx.	3,0 kg
Gross weight approx.	3,8 kg
Shipping weight	3,7 kg
Shipping volume weight	2,6 kg

Product information	
GTIN/EAN number	4045761193406
Trade number	90318080
Warranty Time	36 mon
REACH classification	no prohibited substances

Pictograms

STANDARD



OPTION

