PROFESSIONAL MEASURING
SINCE 1844

KERN


Product brochure

30.10.2026

# KERN EOB 150K50L

Allround parcel scale with robust stainless steel weighing plate

ENGLISH




## CONTACT

**KERN & SOHN GmbH**
**Ziegelei 1**
**72336 Balingen**
**Germany**

**+49 7433 9933-0**
**info@kern-sohn.com**
**www.kern-sohn.com**

## FEATURES

- Weighing plate stainless steel, painted steel base
- Simple and convenient 4-key operation
- Wall mount for display device, standard
- Hold function: When the weighing conditions are unstable, a stable weight is calculated determining an average value
- Protective working cover included with delivery
- Universal external mains adapter included with delivery



## TECHNICAL DATA

- Large LCD display, digit height 25 mm
- Weighing platform dimensions, stainless steel, W×D×H 550×550×58 mm
- Dimensions of display device W×D×H 235×114×51 mm, spiral cable Cable length of display device approx. 2,7 m
- Optional battery operation, 4×1.5 V AA not included in scope of delivery, operating time up to 60 h
- Net weight approx. 13 kg
- Permissible ambient temperature 5 °C/35 °C

## MAIN SCOPE OF APPLICATIONS

As Parcel Scale
- Warehouse logistics
- Production
- Industrial applications

As Veterinary Scale
- Animal weighing

## PICTOGRAMS

Standard




Option




## MODEL OVERVIEW

| Model | Weighing capacity [Max] | Readability [d] | Dimensions weighing surface | Net weight approx. |
|---|---|---|---|---|
| EOB 15K5 | 15 kg | 0,005 kg | 315×305 mm | 3,8 kg |

| Model | Weighing capacity [Max] | Readability [d] | Dimensions weighing surface | Net weight approx. |
|---|---|---|---|---|
| EOB 35K10 | 35 kg | 0,01 kg | 315×305 mm | 3,8 kg |
| EOB 60K20 | 60 kg | 0,02 kg | 315×305 mm | 3,8 kg |
| EOB 60K20L | 60 kg | 0,02 kg | 550×550 mm | 13 kg |
| EOB 150K50 | 150 kg | 0,05 kg | 315×305 mm | 3,8 kg |
| EOB 150K50L | 150 kg | 0,05 kg | 550×550 mm | 13 kg |
| EOB 150K50XL | 150 kg | 0,05 kg | 950×500 mm | 17 kg |
| EOB 300K100A | 300 kg | 0,1 kg | 315×305 mm | 3,8 kg |
| EOB 300K100L | 300 kg | 0,1 kg | 550×550 mm | 13 kg |
| EOB 300K100XL | 300 kg | 0,1 kg | 950×500 mm | 17 kg |

ENGLISH

## ACCESSORIES

| Model | Description |
|---|---|
| EOB-A02B | Tripod EOB-A02B, Height of stand approx. 1000 mm |
| EOB-A04B | Protective working cover EOB-A04B |
| EOB-A04BS05 | Protective working cover EOB-A04BS05, scope of delivery: 5 items |
| EOC-A04 | Wall mount for display device EOC-A04 |
| YKA-16 | Power adapter YKA-16 (9 V, 100 mA \| 100 V - 240 V \| EURO, AUS, UK, US, CH) |

## SERVICES

| Model | Description |
|---|---|
| 961-249 | Adjustment at the location of installation 961-249 (Not in combination with verification) |
| 963-129 | DAkkS calibration certificate 963-129 |
| 969-517 | Confirmation of the manufacturer's specification (only in combination with DAkkS calibration certificate)969-517 |
| 970-015 | Warranty extension (+3 years) 970-015 |
| KIB-M01 | Modification of the display device KERN KIB-M01 (to move the cable outlet to the front of the display device) |

# KERN Pictogram Overview

| | |
|---|---|
|  | External adjustment: Adjusting accuracy using external adjustment weight |
|  | Piece counting: Reference quantities selectable. Display can be switched from piece to weight |
|  | Units can be switched to e.g. non-metric units |
|  | Hold function: When the weighing conditions are unstable, a stable weight is calculated as an average value |
|  | Battery operation: Ready for battery operation |
|  | Universal plug-in power supply: With universal input and optional input socket adapters for EU, CH, GB or EU, CH, GB, US or EU, CH, GB, US, AUS |
|  | Weighing principle Strain gauges: Electrical resistor on an elastic deforming body |
|   | Package shipment by courier service: The duration of internal product provision is one day |
|   | Accredited calibration (DKD): The duration of the accredited calibration is 3 working days |