SAUTER **JIT 200**

Infrared thermometer for industry, environmental engineering and maintenance work



Date of creation: 24.10.2026

Category	
Brand	Sauter
Product category	Environment/ Occupational safety
Product group	Infrared thermometer
Product family	JIT

Measuring System	
Temperature repeatability - measuring range 2	+/- 0,7 °C
Temperature accuracy - measuring range 2	+/- 1,5 °C
Temperature accuracy - measuring range 1	+/- 1,5 °C+0,1 °C/ °C
Temperature - measuring range 3 [Min]	100 °C
Temperature - measuring range 2 [Min]	0 °C
Temperature - measuring range 1 [Min]	-32 °C
Temperature - measuring range 1 [Max]	0 °C
Temperature - measuring range 3 [Max]	1020 °C
Temperature - measuring range 2 [Max]	100 °C
D:S Optic	20:1
Response time	250 ms
Temperature accuracy - measuring range 3	+/- 1,5%
Level of emission [Min]	0,1
Level of emission [Max]	1
Units	°C °F
Temperature [Min] (°C)	-32 °C
Temperature [Max] (°C)	1100 °C
Default unit	°C
Temperature coefficient - measuring range 1	+/- 0,1 °C/ °C
Temperature coefficient - measuring range 2	+/- 0,1 °C/ °C
Temperature coefficient - measuring range 3	+/- 0,1%/ °C
Temperature repeatability - measuring range 1	+/- 0,7 °C
Temperature repeatability - measuring range 3	+/- 0,7%

Construction	
Dimension (W×D×H)	179×127×53 mm
Material	plastic
Laser power	0,001 W
Laser class	2
Column mount possible	✓

Functions	
Hold function	✓
Peak function	✓
Statistic function	✓
Auto-off interval(s) in battery mode/rechargeable battery mode	15 sec
Memory function	✓
Function for averaging	✓
Limit-setting function	✓

Power Supply	
Supplied power supply	Battery
Battery / accumulator type	Alkali(-Manganese)
Battery	9 V block
Battery connection	9V Bloc
Battery operating time	9 h
Battery capacity	560 mAh
Battery voltage	9 V
Battery – Number of cells	1
Battery – Individual weight	47 g
Battery – Total weight	47 g
Battery capacity (Wh)	5,04 Wh
Battery – Tests passed UN 38.3	✓

SAUTER **JIT 200**

Infrared thermometer for industry, environmental engineering and maintenance work

Battery/Accu connected	not connected, enclosed

Services (optional)

Article number for DAkkS calibration	963-296
Article number for factory calibration	961-296

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	225×150×70 mm
Shipping method	Parcel service
Net weight approx.	0,35 kg
Gross weight approx.	0,50 kg
Shipping weight	0,5 kg
Shipping volume weight	0,5 kg

Product information

GTIN/EAN number	4045761367753
Trade number	90251900
Warranty Time	24 mon
REACH classification	no prohibited substances

Pictograms

STANDARD

