PROFESSIONAL MEASURING
SINCE 1844

KERN

Product brochure

30.10.2026

KERN KFP 150V30LM

Platform

ENGLISH



CONTACT

KERN & SOHN GmbH
Ziegelei 1
72336 Balingen
Germany

+49 7433 9933-0
info@kern-sohn.com
www.kern-sohn.com

FEATURES

- Platform: entirely out of stainless steel
- 1 load cell, aluminium, silicone-coated, IP65, OIML-R60-approved, class III, 3000 e
- Level indicator and levelling feet for precise levelling of the scale, fitted as standard, to give the most accurate weighing result

TECHNICAL DATA

- Weighing platform dimensions W×D×H 650×500×136 mm, stainless steel
- Cable length approx. 3 m
- Net weight approx. 26 kg

PICTOGRAMS

Standard



Factory



MODEL OVERVIEW

Model	Weighing capacity [Max]	Readability [d]	Verification value [e]	Minimal load [Min]	Cable length	Dimensions weighing surface	Net weight approx.
KFP 60V30LM	60 kg	2 g	20 g	400 g	3 m	500×400 mm	14 kg
KFP 60V30XLM	60 kg	2 g	20 g	400 g	3 m	650×500 mm	22 kg
KFP 150V30LM	150 kg	5 g	50 g	1 kg	3 m	650×500 mm	26 kg

ACCESSORIES

Model	Description
YGR-01	ESD grounding plug incl. grounding cable YGR-01
YKV-01	Digital weighing transmitter YKV-01
YKV-02	Digital weighing transmitter YKV-02
YRO-03	roller conveyor YRO-03

ENGLISH

SERVICES

Model	Description
963-129	DAkkS calibration certificate 963-129
965-229	Verification / Conformity assessment according to NAWI (2014/31/EU) 965-229
965-403	Cable extension 965-403 (< 4 m)
965-404	Cable extension 965-404 (4–7 m)
965-405	Cable extension 965-405 (7–20 m)
965-412	Assembly of components 965-412 (> 50 kg - 350 kg)
970-106	Warranty extension (+2 years) 970-106

KERN Pictogram Overview

LC IP 67	Load Cell: Protection against dust and water splashes IP67
1 DAY	Package shipment by courier service: The duration of internal product provision is one day
M	Conformity assessment: The duration of the conformity assessment is 3 working days