KERN **MPD 250K100M**

Professional step-on personal floor scale approved as a medical device, verification optional



Date of creation: 24.10.2026

Category

Brand	KERN
Product category	Medical scale
Product group	Personal floor scale
Product family	MPD

Measuring System

Weighing system	Strain gauge
Weighing capacity [Max]	250 kg
Readability [d]	0,1 kg
Reproducibility	0,1 kg
Linearity	± 0,1 kg
Minimum weight [Min] (verifiable)	2 kg
Resolution	2.500
Adjustment options	Adjusting with external weight
Recommended adjusting weight	200 kg (M1)
Stabilization time	3 s
Eccentric loading at 1/3 [Max]	0,1 kg
Conformity assessment possible	✓
Construction type of the scale	Single-range balance
Units	kg
Default unit	kg
Warm-up time	10 min

Display

Display type	LCD
Display backlight	✓
Display digit height	25 mm
Languages of the user interface	Symbol language

Construction

Dimensions completely mounted (W×D×H)	365×490×120 mm
Dimension display device (W×D×H)	200×130×60 mm
Dimensions weighing platform (W×D×H)	365×360×80 mm
Material housing	steel, lacquered
Material weighing plate	plastic
Material display housing	plastic
Level indicator	✓
Levelling feet adjustable	✓

Functions

Auto-off interval(s) in battery mode/rechargeable battery mode	15 sec
Tare function	none
Number of keys for operation	1

Power Supply

Supplied power supply	Power supply & battery function (battery not included)
Power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO UK CH
Plug-in power supply / adapter for countries - optional	EURO AUS UK US CH
Input voltage power supply / power [Max]	100 V - 240 V, 50 / 60 Hz
Power supply cable removable	removable
Input voltage device / power [Max]	12 V, 500 mA
Power socket for mains adapter	Hollow plug, inside plus, Ø outside 5,5 mm, Ø inside 2,5 mm, long 9,5 mm
Battery / accumulator type	Alkali(-Manganese)
Battery	6×1.5 V AA
Battery connection	Pad + Spring
Battery operating time	20 h
Rechargeable battery	MBC-A03

KERN **MPD 250K100M**

Professional step-on personal floor scale approved as a medical device, verification optional

Rechargeable battery operating time - backlight on	20 h
Rechargeable battery operating time - backlight off	40 h
Rechargeable battery charging time	12 h
Rechargeable battery optional	Rchrg. battery optional - intern

Environmental conditions

Ambient temperature [Min]	-10 °C
Ambient temperature [Max]	40 °C
Humity of environment [Max]	80 %
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

Services (optional)

Article number for adjustment at the location of installation	961-249
Article number for conformity assessment	965-129
Article number for DAkkS calibration	963-129
Article number for certificate of conformity	969-517

Packing & Shipping


Delivery time	1 d
Dimensions packaging (W×D×H)	560×440×200 mm
Shipping method	Parcel service
Net weight approx.	9 kg
Gross weight approx.	11 kg
Shipping weight	10,4 kg
Shipping volume weight	9,9 kg

Product information

GTIN/EAN number	4045761192980
Trade number	84231090
Warranty Time	24 mon
REACH classification	no prohibited substances

Pictograms

STANDARD



OPTION



FACTORY



CE
0297