KERN **MPS 200K100PM**

Stylish personal floor scale with BMI function



Date of creation: 23.10.2026

Category	
Brand	KERN
Product category	Medical scale
Product group	Personal floor scale
Product family	MPS

Measuring System	
Weighing system	Strain gauge
Weighing capacity [Max]	200 kg
Measuring range measuring rod (cm)	60-100cm @ 0,1cm ± 0,5cm 100-205cm @ 0,1cm ± 1cm
Readability [d]	0,1 kg
Reproducibility	0,1 kg
Linearity	± 0,1 kg
Minimum weight [Min] (verifiable)	2 kg
Resolution	2.000
Adjustment options	Adjusting with external weight
Recommended adjusting weight	200 kg (M1)
Eccentric loading at 1/3 [Max]	0,1 kg
Conformity assessment possible	✓
Construction type of the scale	Single-range balance
Units	kg
Maximum creep (15 minutes)	200 g
Maximum creep (30 minutes)	400 g
Default unit	kg
Warm-up time	10 min

Display	
Display type	LCD
Display digit height	27 mm
Languages of the user interface	Symbol language

Construction	
Dimensions completely mounted (W×D×H)	275×445×1020 mm
Dimension display device (W×D×H)	215×110×45 mm
Dimensions weighing platform (W×D×H)	275×295×58 mm
Material housing	steel, lacquered
Material weighing plate	steel, lacquered
Material display housing	plastic
Level indicator	✓
Levelling feet adjustable	✓
Stand height	1000 mm

Functions	
Function for BMI calculation	✓
Hold function	✓
PreTare function	✓
Function for averaging under unstable weighing conditions	✓
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min off 4 min 5 min 2 min
Tare function	manual (multi)
Number of keys for operation	20

Interface	
Interfaces	RS-232 standard

Power Supply	
Supplied power supply	Power supply & battery function (battery not included)
Power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO UK CH
Plug-in power supply / adapter for countries - optional	EURO UK

KERN **MPS 200K100PM**

Stylish personal floor scale with BMI function

	US CH
Input voltage power supply / power [Max]	100 V - 240 V, 50 / 60 Hz
Power supply cable removable	removable
Input voltage device / power [Max]	12 V, 500 mA
Power socket for mains adapter	Hollow plug, inside minus, Ø outside 5,5 mm, Ø inside 2,1 mm, long 9,5 mm
Battery	6×1.5 V AA
Battery operating time	50 h
Rechargeable battery	FOB-A08
Rechargeable battery operating time - backlight off	35 h
Rechargeable battery charging time	14 h
Rechargeable battery optional	Rchrg. battery optional - intern

Environmental conditions

Ambient temperature [Min]	5 °C
Ambient temperature [Max]	35 °C
Humity of environment [Max]	80 %
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

Services (optional)

Article number for adjustment at the location of installation	961-249
Article number for DAkkS calibration	963-129
Article number for certificate of conformity	969-517

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	1180×400×330 mm
Shipping method	Parcel service
Net weight approx.	7 kg
Gross weight approx.	11 kg
Shipping weight	31,2 kg
Shipping volume weight	31,2 kg

Product information

GTIN/EAN number	4045761192829
Trade number	84231090
Warranty Time	36 mon
REACH classification	no prohibited substances

Pictograms

STANDARD



OPTION

