KERN **OBE 134C825**

Our all-round compound microscope as a comprehensive digital solution for schools, training and laboratories

Date of creation: 14.11.2026

Category	
Brand	Optics
Product category	Microscope
Product group	Digital microscope set
Product family	OBE-S

Construction	
Dimension (W×D×H)	360×150×390 mm
Optical system	Finite
Tube type	Trinocular
Tube angle of inclination	30°
Tube 360° rotation	✓
Tube type	Butterfly
Light distribution	20:80
Contrasting methods	Bright field Darkfield (optional)
Standard objectives	4× 10× 40× 100×
Lens quality	achromatic
Nosepiece screw-in locations	4
Eyepieces fixed	✓
Interpupillary distance [Min]	50 mm
Interpupillary distance [Max]	75 mm
Diopter adjustment	one-sided
Diopter adjustment [Min]	-5
Diopter adjustment [Max]	5
Colour temperature	5500 K

Functions	
Supported operating systems	Win XP Win Vista Win 7 Win 8 Win 10
Camera - Applicable software	Microscope VIS 2.0 Pro (OXM 902)

Interface	
Interfaces	USB 2.0

Ocular	
Ocular field width	HWF
Eye point	High Eye Point
Ocular magnifications	10x
Ocular visual field	18 mm
Ocular diameter	23,2 mm

Illumination	
Illuminance	Transmitted light
Illumination type transmitted light	LED
Illumination intensity transmitted light	3 W
Illumination dimmable	Transmitted light
Filter possible	✓

80000	Mikroskoptisch	
Weg		50 mm; 70 mm
Durchlicht möglich		✓
ATTR_microscopeTableSpecimentHolders		1

Focussing	
Field of view [Min]	0,18 mm
Field of view [Max]	4,5 mm
Torque regulation	✓
Fine drive minimum	0,002 mm
Focusing mechanism	coaxial coarse and fine drive

Condensor	
Condensor type	Abbe
Condenser - Mounting	fixed
Condenser - Aperture	1,25
Aperture diaphragm	✓

KERN **OBE 134C825**

Our all-round compound microscope as a comprehensive digital solution for schools, training and laboratories

Camera

Cameratype	USB2 Microscope camera - C-Mount
Camera - Resolution	5,1 MP
Camera - Sensor type	CMOS
Camera - Sensor size	1/2,5"
Camera - Colour depth	Colour
Camera - Framerate	6,8 - 55 fps
Camera- Mounting types	C-mount thread
Camera - Exposure method	Rolling Shutter

Power Supply

Supplied power supply	Power supply unit
Power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO
Plug-in power supply / adapter for countries - optional	AUS UK US CH
Input voltage power supply / power [Max]	100 - 240 V
Power supply cable removable	removable
Input voltage device / power [Max]	5 V, 1 A

Environmental conditions

Storage temperature [Min]	-5 °C
Storage temperature [Max]	40 °C

Approval

CE mark	✓

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	560×440×330 mm
Shipping method	Parcel service
Net weight approx.	6 kg
Gross weight approx.	8 kg
Shipping weight	16,3 kg
Shipping volume weight	16,3 kg

Product information

GTIN/EAN number	4045761356795
Trade number	90118000
Warranty Time	36 mon
REACH classification	no prohibited substances

Pictograms

STANDARD

OPTION