# KERN **OBE 134C832**

Our all-round compound microscope as a comprehensive digital solution for schools, training and laboratories



**Date of creation: 24.10.2026**

| Category | |
|---|---|
| Brand | Optics |
| Product category | Microscope |
| Product group | Digital microscope set |
| Product family | OBE-S |

| Construction | |
|---|---|
| Dimension (W×D×H) | 360×150×390 mm |
| Optical system | Finite |
| Tube type | Trinocular |
| Tube angle of inclination | 30° |
| Tube 360° rotation | ✓ |
| Tube type | Butterfly |
| Light distribution | 20:80 |
| Contrasting methods | Bright field<br>Darkfield (optional) |
| Standard objectives | 4×<br>10×<br>40×<br>100× |
| Lens quality | achromatic |
| Nosepiece screw-in locations | 4 |
| Eyepieces fixed | ✓ |
| Interpupillary distance [Min] | 50 mm |
| Interpupillary distance [Max] | 75 mm |
| Diopter adjustment | one-sided |
| Diopter adjustment [Min] | -5 |
| Diopter adjustment [Max] | 5 |
| Colour temperature | 5500 K |

| Functions | |
|---|---|
| Supported operating systems | Win XP<br>Win Vista<br>Win 7<br>Win 8<br>Win 10 |
| Camera - Applicable software | Microscope VIS 2.0 Pro (OXM 902) |

| Interface | |
|---|---|
| Interfaces | USB 3.0 |

| Ocular | |
|---|---|
| Ocular field width | HWF |
| Eye point | High Eye Point |
| Ocular magnifications | 10x |
| Ocular visual field | 18 mm |
| Ocular diameter | 23,2 mm |

| Illumination | |
|---|---|
| Illuminance | Transmitted light |
| Illumination type transmitted light | LED |
| Illumination intensity transmitted light | 3 W |
| Illumination dimmable | Transmitted light |
| Filter possible | ✓ |

| 80000 \| Mikroskoptisch | |
|---|---|
| Durchlicht möglich | ✓ |

| Focussing | |
|---|---|
| Field of view [Min] | 0,18 mm |
| Field of view [Max] | 4,5 mm |
| Torque regulation | ✓ |
| Fine drive minimum | 0,002 mm |
| Focusing mechanism | coaxial coarse and fine drive |

| Condensor | |
|---|---|
| Condensor type | Abbe |
| Condenser - Mounting | fixed |
| Condenser - Aperture | 1,25 |
| Aperture diaphragm | ✓ |

# KERN **OBE 134C832**

Our all-round compound microscope as a comprehensive digital solution for schools, training and laboratories

## Camera

| | |
|---|---|
| Cameratype | USB3 Microscope camera - C-Mount |
| Camera - Resolution | 5,1 MP |
| Camera - Sensor type | CMOS |
| Camera - Sensor size | 1/2,5" |
| Camera - Colour depth | Colour |
| Camera - Framerate | 14,2 - 101,2 fps |
| Camera- Mounting types | C-mount thread |
| Camera - Exposure method | Rolling Shutter |

## Power Supply

| | |
|---|---|
| Supplied power supply | Power supply unit |
| Power supply type | Power adapter |
| Plug-in power supply / adapter for countries - included with the delivery | EURO |
| Plug-in power supply / adapter for countries - optional | AUS<br>UK<br>US<br>CH |
| Input voltage power supply / power [Max] | 100 - 240 V |
| Power supply cable removable | removable |
| Input voltage device / power [Max] | 5 V, 1 A |

## Environmental conditions

| | |
|---|---|
| Storage temperature [Min] | -5 °C |
| Storage temperature [Max] | 40 °C |

## Packing & Shipping

| | |
|---|---|
| Delivery time | 1 d |
| Dimensions packaging (W×D×H) | 560×440×330 mm |
| Shipping method | Parcel service |
| Net weight approx. | 6 kg |
| Gross weight approx. | 8 kg |
| Shipping weight | 16,3 kg |
| Shipping volume weight | 16,3 kg |

## Product information

| | |
|---|---|
| GTIN/EAN number | 4045761356801 |
| Trade number | 90118000 |
| Warranty Time | 36 mon |
| REACH classification | no prohibited substances |

## Pictograms

**STANDARD**




**OPTION**

