# KERN **ORM 1CO**

Digital measurement of refraction index for universal application




**Date of creation: 13.11.2026**

| Category | |
|---|---|
| Brand | Optics |
| Product category | Refractometer |
| Product group | Digital refractometer |
| Product family | ORM-CO |

| Measuring System | |
|---|---|
| Scales | Refractive index<br>Brix<br>Kaffee TDS 1 |
| Measurement temperature [Max] (°C) | 40 °C |
| Measurement temperature [Min] (°C) | 0 °C |
| Readabilites [d] | 0,0001 nD<br>0,1 %<br>0,1 |
| Precision | 0,0003 nD<br>0,2 %<br>0,2 |
| Appropriate calibration liquid | 0 % (distilled water) |
| Measuring method | Total reflection |
| Automatic temperature compensation (ATC) | ✓ |
| Measuring range refractive index [Min] | 1,3330 nD |
| Measuring range refractive index [Max] | 1,4200 nD |
| Readout refractive index | 0,0001 nD |
| Accuracy refractive index | ±0,0003 nD |
| Scale for Refractive index | ✓ |
| Measuring range coffee TDS 1 [Min] | 0 % |
| Measuring range coffee TDS 1 [Max] | 25 % |
| Readout coffee TDS 1 | 0,1 % |
| Accuracy coffee TDS 1 | ±0,2 % |
| Scale coffee TDS 1 | ✓ |
| Measuring ranges | 1,3330 nD - 1,4200 nD<br>0,0 % - 50,0 %<br>0,0 - 25,0 |
| Area of application | Coffee |
| Accuracy Brix | ±0,2 % |
| Readout Brix | 0,1 % |
| Measuring range Brix [Min] | 0 % |
| Measuring range Brix [Max] | 50 % |
| Brix scale | ✓ |

| Construction | |
|---|---|
| Dimension (W×D×H) | 121×58×25 mm |
| Refractometer type | Handheld refractometer |
| Scale - Display type | Digital |
| Prism lid | ✓ |
| Material prism | ZLaF3 lanthanum flint glass nd=1.85544 |

| Functions | |
|---|---|
| IP protection - complete device | IP65 |
| Auto-off interval(s) in battery mode/rechargeable battery mode | 60 sec |
| Averaging measurement | ✓ |
| Averaging measurement amount | 15 |

| Power Supply | |
|---|---|
| Supplied power supply | Battery |
| Power supply cable removable | removable |
| Battery / accumulator type | Alkali(-Manganese) |
| Battery connection | Pad + Spring |
| Battery capacity | 1.300 mAh |
| Battery voltage | 1,5 V |
| Battery – Number of cells | 1 |
| Battery – Individual weight | 11,5 g |
| Battery – Total weight | 11,5 g |
| Battery – Construction | Individual cells |
| Battery capacity (Wh) | 1,95 Wh |
| Battery – Lithium content | 0 g |
| Battery/Accu connected | not connected, enclosed |

# KERN **ORM 1CO**

Digital measurement of refraction index for universal application

| Environmental conditions | |
|---|---|
| Storage temperature [Min] | -5 °C |
| Storage temperature [Max] | 40 °C |

| Approval | |
|---|---|
| CE mark | ✓ |

| Services (optional) | |
|---|---|
| Article number for factory calibration | 961-290 |

| Packing & Shipping | |
|---|---|
| Dimensions transport container (W×D×H) | 170×110×50 mm |
| Delivery time | 1 d |
| Dimensions packaging (W×D×H) | 170×110×50 mm |
| Shipping method | Parcel service |
| Net weight approx. | 0,15 kg |
| Gross weight approx. | 0,35 kg |
| Shipping weight | 0,31 kg |
| Shipping volume weight | 0,2 kg |

| Product information | |
|---|---|
| GTIN/EAN number | 4045761335493 |
| Trade number | 90275000 |
| Warranty Time | 24 mon |
| REACH classification | no prohibited substances |

## Pictograms

### STANDARD




### OPTION

