KERN **ORM 1UN**

Digital measurement of refraction index for universal application



Date of creation: 14.11.2026

Category	
Brand	Optics
Product category	Refractometer
Product group	Digital refractometer
Product family	ORM-UN

Measuring System	
Scales	Refractive index Brix Urine (spec. gravity) Serum proteine
Measurement temperature [Max] (°C)	40 °C
Measurement temperature [Min] (°C)	0 °C
Readabilites [d]	0,0001 nD 0,1 % 0,001 sgU 0,1 g/dl
Precision	0,0003 nD 0,2 % 0,002 sgU 0.2 g/dl
Appropriate calibration liquid	0 % (distilled water)
Measuring method	Total reflection
Automatic temperature compensation (ATC)	✓
Scale urine (specific gravity)	✓
Measuring range refractive index [Min]	1,3330 nD
Measuring range refractive index [Max]	1,4200 nD
Readout refractive index	0,0001 nD
Accuracy refractive index	±0,0003 nD
Scale for Refractive index	✓
Measuring range protein serum [Min]	0 g/100 ml
Measuring range protein serum [Max]	12 g/100 ml
Readout protein serum	0,1 g/100 ml
Accuracy protein serum	±0,2 g/100 ml
Scale protein serum	✓
Measuring range urine (specific gravity) [Min]	1,000
Measuring range urine (specific gravity) [Max]	1,050
Readout urine (specific gravity)	0,001
Accuracy urine (specific gravity)	±0,002
Measuring ranges	1,3330 nD - 1,4200 nD 0,0 % - 50,0 % 1,000 sgU - 1,050 sgU 0,0 g/dl - 12,0 g/dl
Area of application	Urine
Accuracy Brix	±0,2 %
Readout Brix	0,1 %
Measuring range Brix [Min]	0 %
Measuring range Brix [Max]	50 %
Brix scale	✓

Construction	
Dimension (W×D×H)	121×58×25 mm
Refractometer type	Handheld refractometer
Scale - Display type	Digital
Prism lid	✓
Material prism	ZLaF3 lanthanum flint glass nd=1.85544

Functions	
IP protection - complete device	IP65
Auto-off interval(s) in battery mode/rechargeable battery mode	60 sec
Averaging measurement	✓
Averaging measurement amount	15

Power Supply	
Supplied power supply	Battery
Power supply cable removable	removable
Battery / accumulator type	Alkali(-Manganese)
Battery connection	Pad + Spring

KERN **ORM 1UN**

Digital measurement of refraction index for universal application

Battery capacity	1.300 mAh
Battery voltage	1,5 V
Battery – Number of cells	1
Battery – Individual weight	11,5 g
Battery – Total weight	11,5 g
Battery – Construction	Individual cells
Battery capacity (Wh)	1,95 Wh
Battery – Lithium content	0 g
Battery/Accu connected	not connected, enclosed

Environmental conditions

Storage temperature [Min]	-5 °C
Storage temperature [Max]	40 °C

Approval

CE mark	✓

Services (optional)

Article number for factory calibration	961-290

Packing & Shipping

Dimensions transport container (W×D×H)	170×110×50 mm
Delivery time	1 d
Dimensions packaging (W×D×H)	170×110×50 mm
Shipping method	Parcel service
Net weight approx.	0,15 kg
Gross weight approx.	0,35 kg
Shipping weight	0,31 kg
Shipping volume weight	0,2 kg

Product information

GTIN/EAN number	4045761335561
Trade number	90275000
Warranty Time	24 mon
REACH classification	no prohibited substances

Pictograms

STANDARD



OPTION

