# KERN PCB 10000-1-Rez



Upgrade your laboratory balance to a high-end recipe balance for the pharmaceutical, chemical and food industries





| Category          |                         |
|-------------------|-------------------------|
| Brand             | KERN                    |
| Product categoriy | Balance software bundle |
| Product group     | Recipe balance          |
| Product family    | PCB-Rez                 |

| Measuring System                               |                   |
|--|-------------------|
| Weighing system                                | Strain gauge      |
| Weighing capacity [Max]                        | 10 kg             |
| Readability [d]                                | 100 mg            |
| Reproducibility                                | 100 mg            |
| Linearity                                      | ± 300 mg          |
| USP Minimum weight of sample (k = 2, U = 0.1%) | 200 g             |
| Resolution                                     | 100.000           |
| Recommended adjusting weight                   | 10 kg (F1)        |
| Possible calibration points                    | 2 kg; 5 kg; 10 kg |
| Stabilization time                             | 3 s               |
| Warm-up time                                   | 120 min           |
| Eccentric loading at 1/3 [Max]                 | 400 mg            |
| Maximum creep (15 minutes)                     | 1 g               |
| Maximum creep (30 minutes)                     | 2 g               |

| Construction                      |               |
|-----------------------------------|---------------|
| Dimension housing (W×D×H)         | 163×245×65 mm |
| Dimensions weighing surface (W×D) | 150×170 mm    |
| Dimensions weighing surface       | 150×170 mm    |
| Level indicator                   | ✓             |
| Levelling feet adjustable         | ✓             |

| Functions   |          |
|---|----------|
| Counting resolution (laboratory conditions)                       | 50.000   |
| Counting reference weight can be entered                          | <b>✓</b> |
| Smallest piece weight when piece counting - laboratory conditions | 200 mg   |

Smallest piece weight when piece counting - normal conditions 2 g

| •   |                |
|---|----------------|
| Interface   |                |
| EasyTouch (ET) - Compatibility                              | Vollständig    |
| Power Supply  |                |
| Battery operating time                                      | 20 h           |
| Rechargeable battery operating time - backlight on          | 24 h           |
| Rechargeable battery operating time - backlight off         | 48 h           |
| Rechargeable battery charging time                          | 8 h            |
| Environmental conditions                                    |                |
| Ambient temperature [Min]                                   | -10 °C         |
| Ambient temperature [Max]                                   | 40 °C          |
| Humity of environment [Max]                                 | 80 %           |
| Storage temperature [Min]                                   | -20 °C         |
| Storage temperature [Max]                                   | 60 °C          |
| Approval  |                |
| CE mark   | ✓              |
| Services (optional)   |                |
| Article number for DAkkS calibration                        | 963-128        |
| Article number for certificate of conformity (verification) | 969-517        |
| Packing & Shipping  |                |
| Delivery time   | 1 d            |
| Dimensions packaging (W×D×H)                                | 235×365×175 mm |
| Shipping method   | Parcel service |
| Net weight approx.  | 1,4 kg         |
| Gross weight approx.  | 2,4 kg         |
| Shipping weight   | 3 kg           |

1

## KERN PCB 10000-1-Rez



Upgrade your laboratory balance to a high-end recipe balance for the pharmaceutical, chemical and food industries

## Pictograms

### **STANDARD**



### **OPTION**

