PROFESSIONAL MEASURING
SINCE 1844

KERN

Product brochure

30.10.2026

KERN RIB 30K-2M

Robust retail scale with large item memory and user-friendly handling, verification optional

ENGLISH



CONTACT

KERN & SOHN GmbH
Ziegelei 1
72336 Balingen
Germany

+49 7433 9933-0
info@kern-sohn.com
www.kern-sohn.com



FEATURES

- Second display on the back of the balance
- Three displays for weight display (verifiable), unit price, total price
- 10 direct price keys for frequently recurring article prices
- Memory (PLU) for 20 article prices
- Energy management: Backlight turns off after 5 sec, can be switched off
- Soil-resistant construction through water channels at the frame of the housing and sealing rings over the upper housing inlets
- Protective working cover included with delivery

TECHNICAL DATA

- Large backlit LCD displays, digit height 18 mm
- Dimensions weighing surface, stainless steel, W×D 294×225 mm
- Overall dimensions W×D×H 325×340×115 mm
- Net weight approx. 3,2 kg
- Permissible ambient temperature -10 °C/40 °C

MAIN SCOPE OF APPLICATIONS

- Retail
- retail shops
- Gastronomy
- Weekly markets
- farm shops
- Fruit and vegetable sales
- Food industry
- Packaging industry

PLEASE NOTE FOR YOUR ORDER

- Official verification is mandatory for commercial trade
- For devices that require verification (conformity assessment according to NAWI 2014/31/EU), please include the verification when placing your order, the initial verification is not possible after delivery. Please inform the full address of the location of use for the initial verification

PICTOGRAMS

Standard | Option | Factory



MODEL OVERVIEW

Model	Weighing capacity [Max]	Readability [d]	Dimensions weighing surface	Net weight approx.
RIB 6K-3HM	3 kg; 6 kg	0,001 kg; 0,002 kg	315×225 mm	3,8 kg
RIB 6K-3M	3 kg; 6 kg	0,001 kg; 0,002 kg	294×225 mm	3,2 kg
RIB 10K-3HM	6 kg; 15 kg	0,002 kg; 0,005 kg	315×225 mm	3,8 kg
RIB 10K-3M	6 kg; 15 kg	0,002 kg; 0,005 kg	294×225 mm	3,2 kg
RIB 30K-2HM	15 kg; 30 kg	0,005 kg; 0,01 kg	294×225 mm	3,8 kg
RIB 30K-2M	15 kg; 30 kg	0,005 kg; 0,01 kg	294×225 mm	3,2 kg

ACCESSORIES

Model	Description
GAB-A04	Rechargeable battery pack GAB-A04 (Pb)
RIB-A01	Protective working cover RIB-A01
YKA-20	Power adapter YKA-20 (12 V, 1000 mA | 100 V - 240 V AC 50/60 Hz 0.4 A max | EURO, UK, US)

SERVICES

Model	Description
961-248	Adjustment at the location of installation 961-248 (Not in combination with verification)
963-128	DAkkS calibration certificate 963-128
965-228	Verification / Conformity assessment according to NAWI (2014/31/EU) 965-228
969-517	Confirmation of the manufacturer's specification (only in combination with DAkkS calibration certificate)969-517

Model	Description
970-014	Warranty extension (+3 years) 970-014

KERN Pictogram Overview

	External adjustment: Adjusting accuracy using external adjustment weight
	Memory: Device-internal memory capacity, e.g. for article data, measuring data, tare weights, PLU etc.
	Rechargeable battery pack: Rechargeable set
	Plug-in power supply: 230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available
	Weighing principle Strain gauges: Electrical resistor on an elastic deforming body
	Package shipment by courier service: The duration of internal product provision is one day
	Accredited calibration (DKD): The duration of the accredited calibration is 3 working days
	Conformity assessment: The duration of the conformity assessment is 3 working days

ENGLISH