

KERN RIB 30K-2M

Robust retail scale with large item memory and user-friendly handling, verification optional



Category

Brand	KERN
Product category	Industrial scale
Product group	Price computing scale
Product family	RIB

Measuring System

Weighing system	Strain gauge
Number of weighing ranges	2
Weighing capacity [Max]	15 kg; 30 kg
Readability [d]	0,005 kg; 0,01 kg
Reproducibility	0,005 kg; 0,01 kg
Linearity	± 0,005 kg; 0,01 kg
Minimum weight [Min] (verifiable)	0,1 kg; 0,2 kg
Resolution	3.000, 3.000
Tare range	30 kg
Adjustment options	Adjusting with external weight
Recommended adjusting weight	30 kg (M1)
Possible calibration points	30 kg
Stabilization time	2 s
Eccentric loading at 1/3 [Max]	0,005 kg; 0,01 kg
Conformity assessment possible	✓
Construction type of the scale	Multi-range balance
Units	kg
Units (if device is conformity assessed)	kg
Default unit	kg
Loadcell type	aluminium IP65 silicone-coated

Display

Display type	LCD
Display backlight	✓
Display segments	7
Display digit height	18 mm
Additional display	18 mm Stative

Construction

Dimension housing (W×D×H)	325×340×115 mm
Dimensions completely mounted (W×D×H)	325×340×115 mm
Dimensions weighing surface (W×D)	294×225 mm
Dimensions weighing surface	294×225 mm
Material housing	plastic
Material weighing plate	stainless steel
Material platform	plastic
Material display housing	plastic
Material load cell(s)	aluminium
Level indicator	✓
Levelling feet adjustable	✓

Functions

Function for price calculation	✓
PLU - direct keys	10
PLU - total	20
Underfloor weighing	None
IP protection - load cell	IP65
Memory function	✓
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min off 5 min 10 min
Auto-off interval(s) in mains power mode	3 min off 30 min selectable 15 min
Tare function	manual (single)
Number of keys for operation	33

Power Supply

Supplied power supply	Accu & Power supply
Power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO UK CH

KERN RIB 30K-2M

KERN

Robust retail scale with large item memory and user-friendly handling, verification optional

Plug-in power supply / adapter for countries - optional	EURO AUS UK US CH
Input voltage power supply / power [Max]	100 V - 240 V AC 50/60 Hz 0.4 A max
Power supply cable removable	removable
Input voltage device / power [Max]	12 V, 1000 mA
Power socket for mains adapter	Inside plus, outside minus
Battery / accumulator type	Pb
Battery	no battery
Battery connection	Plug-in terminals
Battery - Individual weight	741,8 g
Rechargeable battery	6 V, 4 Ah
Rechargeable battery operating time - backlight on	40 h
Rechargeable battery operating time - backlight off	80 h
Rechargeable battery charging time	14 h
Battery/Accu connected	fixed electrical connection, not insulated

Environmental conditions

Ambient temperature [Min]	-10 °C
Ambient temperature [Max]	40 °C
Humidity of environment [Min]	0 %
Humidity of environment [Max]	80 %

Approval

CE mark	✓
Conformity assessment possible ex works	✓
Accuracy classe	III
Verification scale interval [e]	0,005 kg; 0,01 kg

Services (optional)

Article number for adjustment at the location of installation	961-248
Article number for conformity assessment	965-228
Article number for DAkkS calibration	963-128
Article number for certificate of conformity	969-517

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	380×380×155 mm
Shipping method	Parcel service
Net weight approx.	3,2 kg
Gross weight approx.	4,6 kg
Shipping weight	4,5 kg
Shipping volume weight	4,5 kg

Product information

GTIN/EAN number	404576 1180796
Trade number	84238 125
REACH classification	no prohibited substances

Pictograms

STANDARD



OPTION



FACTORY

