


KERN ABP 100-4M

Premium analytical balance with the latest Single-Cell Generation for extremely rapid, stable weighing results



Units	g mg ct
Units (if device is conformity assessed)	g mg ct
Conformity assessment possible	✓

Display	
Display type	OLED
Display type	OLED
Display backlight	LED is self-luminous
Display segments	7
Display digit height	12 mm
Languages of the user interface	German English

Construction	
Dimension housing (W×D×H)	220×370×350 mm
Dimensions rectangular draught shield - inner (W×D×H)	166×156×220 mm
Dimensions rectangular draught shield - outer (W×D×H)	213×156×225 mm
Dimensions weighing surface (∅)	91 mm
Dimensions weighing surface	91 mm
Material housing	cast aluminium, plastic
Material weighing plate	stainless steel
Material platform	Stainless steel
Material draught shield	glass
Level indicator	✓
Levelling feet adjustable	✓

Functions	
Sum memory function	✓
Recipe/summing level	Rez B (Net-total, memory with plain text designations + setpoint, also for printout)
Recipe weighing - number of database entries	5
Recipe weighing - number of ingredients per database entry	10
Percentage determination	✓
Tolerance weighing	✓
Tolerance weighing - type of signal	visual
Underfloor weighing	Hook (included in delivery)
Function for averaging under unstable weighing conditions	✓

Category	
Brand	KERN
Product category	Laboratory balance
Product group	Analytical balance
Product family	ABP

Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Single-Cell
Weighing capacity [Max]	120 g
Weighing capacity [Max] (ct)	600 ct
Readability [d]	0,0001 g
Readability carat [d] (ct)	0,001 ct
Reproducibility	0,0001 g
Linearity	± 0,0002 g
USP Minimum weight of sample (k = 2, U = 0.1%)	200 mg
Minimum weight [Min]	0,01 g
Minimum weight [Min] (ct)	0,1 ct
Resolution	1.200.000
Tare range	120 g
Adjustment options	Internal calibration (automatic) Adjusting with internal weight (manual)
Automatic adjustment - Standard temperature deviation	1 °C
Automatic adjustment - Standard time interval	4 h
Stabilization time	2 s
Warm-up time	8 h
Eccentric loading at 1/3 [Max]	0,0003 g
Default unit	g

KERN ABP 100-4M



Premium analytical balance with the latest Single-Cell Generation for extremely rapid, stable weighing results

Capacity - Display	✓
Standby function	✓
Counting function	✓
Counting resolution (laboratory conditions)	120.000
Counting reference weight can be entered	✓
Smallest piece weight when piece counting - laboratory conditions	1 mg
Smallest piece weight when piece counting - normal conditions	10 mg
Reference quantity	10, 20, 50, 100
Tare function	manual (multi)
Number of keys for operation	11

Interface

Interfaces	RS-232 standard USB-Host/Master USB-Device
------------	--

Power Supply

Supplied power supply	Power supply unit
Plug-in power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO
	AUS
	UK
	US
Plug-in power supply / adapter for countries - optional	CH
	EURO
	UK
Input voltage power supply / power [Max]	US
	CH
	220 V - 240 V AC, 50 Hz
Input voltage device / power [Max]	12 V, 1 A

Environmental conditions

Ambient temperature [Min]	10 °C
Ambient temperature [Max]	30 °C
Humidity of environment [Max]	80 %
Storage temperature [Min]	-10 °C
Storage temperature [Max]	50 °C

Approval

CE mark	✓
Conformity assessment possible ex works	✓
Accuracy classe	I
Verification scale interval [e]	0,001 g

Verification scale interval [e] (ct)	0,01 ct
--------------------------------------	---------

Services (optional)


Article number for conformity assessment	965-201
Article number for DAkkS calibration	963-101
Article number for certificate of conformity	969-517

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	382×585×535 mm
Shipping method	Parcel service
Net weight approx.	8 kg
Gross weight approx.	11 kg
Shipping weight	23,9 kg

Pictograms

STANDARD



OPTION



FACTORY

