
KERN **ACJ 100-4M**

The bestseller in analytical balances, with high-quality single-cell weighing system, verification optional



Date of creation: 24.10.2026

Category

Brand	KERN
Product category	Laboratory balance
Product group	Analytical balance
Product family	ACJ

Measuring System

Weighing system	Single-Cell
Weighing capacity [Max]	120 g
USP Minimum weight of sample (k = 2, U = 0.1%)	400 mg
Readability [d]	0,0001 g
Automatic adjustment - Standard temperature deviation	2 °C
Automatic adjustment - Standard time interval	4 h
Reproducibility	0,0002 g
Linearity	± 0,0003 g
Minimum weight [Min] (verifiable)	0,01 g
Resolution	1.200.000
Adjustment options	Internal calibration (automatic) Adjusting with internal weight (manual)
Recommended adjusting weight	100 g (E2)
Stabilization time	3 s
Eccentric loading at 1/3 [Max]	0,0005 g
Weighing capacity [Max] (ct)	600 ct
Conformity assessment possible	✓
Construction type of the scale	Single-range balance
Units	g mg ct
Units (if device is conformity assessed)	g mg ct
Default unit	g
Minimum weight [Min] (ct)	0,1 ct
Readability carat [d] (ct)	0,001 ct
Warm-up time	8 h
typical reproducibility	0,00006 g
typical USP Minimum weight of sample	120 mg

Display

Display type	LCD
Display type	LCD
Display backlight	no
Display screen size	115×32 mm
Display digit height	14 mm
Languages of the user interface	Symbol language

Construction

Dimension housing (W×D×H)	213×333×338 mm
Dimensions rectangular draught shield - inner (W×D×H)	174×162×227 mm
Dimensions rectangular draught shield - outer (W×D×H)	201×220×256 mm
Dimensions weighing surface (Ø)	91 mm
Dimensions weighing surface	91 mm
Material housing	cast aluminium, plastic
Material weighing plate	stainless steel
Material draught shield	glass
Material display housing	plastic
Level indicator	✓
Levelling feet adjustable	✓

Functions

Density determination	✓
Percentage determination	✓
Standby function	✓
Tolerance weighing	✓
Counting function	✓
Auto-off interval(s) in mains power mode	0 - 99 min
Tare function	manual (multi)

KERN **ACJ 100-4M**

The bestseller in analytical balances, with high-quality single-cell weighing system, verification optional

Counting resolution (laboratory conditions)	120.000
Counting reference weight can be entered	✓
Smallest piece weight when piece counting - laboratory conditions	1 mg
Reference quantity	5, 10, 20, 50, 100
Recipe/summing level	Rez A (Net total)
Number of keys for operation	6
Smallest piece weight when piece counting - normal conditions	10 mg
Tolerance weighing - type of signal	visual

Interface

Interfaces	RS-232 standard USB-Device

Power Supply

Supplied power supply	Power supply unit
Power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO AUS UK US CH
Plug-in power supply / adapter for countries - optional	EURO UK US CH
Input voltage power supply / power [Max]	110 V - 230 V AC
Power supply cable removable	removable
Input voltage device / power [Max]	12 V, 1 A
Power socket for mains adapter	Hollow plug, inside minus, Ø outside 5,5 mm, Ø inside 2,1 mm, long 9,5 mm

Environmental conditions

Ambient temperature [Min]	10 °C
Ambient temperature [Max]	30 °C
Humity of environment [Min]	20 %
Humity of environment [Max]	85 %
Storage temperature [Min]	-10 °C
Storage temperature [Max]	50 °C

Services (optional)

Article number for conformity assessment	965-201
Article number for DAkkS calibration	963-101
Article number for certificate of conformity	969-517

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	390×563×515 mm
Shipping method	Parcel service
Net weight approx.	7 kg
Gross weight approx.	10 kg
Shipping weight	22,6 kg
Shipping volume weight	22,6 kg

Product information

GTIN/EAN number	4045761235649
Trade number	90160010
Warranty Time	36 mon
REACH classification	no prohibited substances

Pictograms

STANDARD



OPTION



FACTORY

