


KERN CCA 6K-5M

High-resolution counting system to count the smallest parts in large quantities, maximum number of parts which can be displayed is 999,999, verification optional



Display backlight	✓
Display digit height	20 mm

Construction

Dimensions weighing surface (W×D)	300×240 mm
Dimensions weighing surface	300×240 mm
Dimensions weighing platform (W×D×H)	300×240×105 mm
Material housing	plastic
Material weighing plate	metal, lacquered
Material load cell(s)	aluminium
Level indicator	✓
Levelling feet adjustable	✓
Transport safety lock - bolt torque	0,1 Nm
Cable length	1,5 m
Display device cable length	5 m

Functions

PreTare function	✓
Sum memory function	✓
Recipe/summing level	Rez A (Net total)
Conversion function	✓
PLU - total	100
Tolerance weighing	✓
Tolerance weighing - type of signal	acoustically visual
Counting function	✓
Counting resolution (laboratory conditions)	300.000
Counting reference weight can be entered	✓
Smallest piece weight when piece counting - laboratory conditions	20 mg
Smallest piece weight when piece counting - normal conditions	200 mg
Reference quantity	5, 10, 20, 50, 100
IP protection - complete device	IP23
IP protection - platform	IP65
IP protection - load cell	IP65
Memory function	✓
Tare function	manual (multi)
Number of keys for operation	28

Interface

Interfaces	RS-232 standard
------------	-----------------

Category

Brand	KERN
Product category	Industrial scale
Product group	Counting system
Product family	CCA

Measuring System

Weighing system	Strain gauge
Reference scale - Weighing capacity [Max]	0,6 kg
Linearity	±
Adjustment options	Adjusting with external weight
Recommended adjusting weight	6 kg (M1)
Quantity scale - Item number	IFS 6K-3M
Stabilization time	2 s
Reference scale - Eccentric loading at 1/3 [Max]	30 mg
Quantity scale - Linearity	0,001 kg; 0,002 kg
Quantity scale - Eccentric loading at 1/3 [Max]	0,001 kg; 0,002 kg
Conformity assessment possible	no
Quantity scale - Reproducibility	0,001 kg; 0,002 kg
Reference scale - Reproducibility	10 mg
Reference scale - item number	TEWJ 600-2M-B
Reference scale - Linearity	30 mg
Units	kg
Units (if device is conformity assessed)	kg
Default unit	kg
Quantity scale - Readability [d]	0,001 kg; 0,002 kg
Quantity scale - Weighing capacity [Max]	3 kg; 6 kg
Reference scale - Readability [d]	10 mg

Display

Display type	LCD
--------------	-----

KERN CCA 6K-5M

KERN

High-resolution counting system to count the smallest parts in large quantities, maximum number of parts which can be displayed is 999,999, verification optional

Power Supply

Supplied power supply Power supply unit

Power supply type Power adapter

Plug-in power supply / adapter for countries - included with the delivery EURO
UK
US
CH

Plug-in power supply / adapter for countries - optional EURO
AUS
UK
US
CH

Input voltage power supply / power [Max] 100 - 240 V

Input voltage device / power [Max] 12 V, 500 mA

Power socket for mains adapter Inside plus, outside minus

Battery / accumulator type Pb

Battery connection Plug-in terminals

Rechargeable battery operating time - backlight on 8 h

Rechargeable battery operating time - backlight off 18 h

Rechargeable battery charging time 12 h

Environmental conditions

Ambient temperature [Min] 0 °C

Ambient temperature [Max] 40 °C

Humidity of environment [Min] 0 %

Humidity of environment [Max] 80 %

Storage temperature [Min] -20 °C

Storage temperature [Max] 60 °C

Approval

CE mark ✓

Conformity assessment possible ex works ✓

Services (optional)

Article number for conformity assessment 965-228-216

Article number for DAkkS calibration 962-128-127

Article number for certificate of conformity 969-517

Packing & Shipping

Delivery time 4 d

Dimensions packaging (W×D×H) 695×405×495 mm

Shipping method Parcel service

Net weight approx. 9 kg

Gross weight approx. 11 kg

Shipping weight 27,9 kg

Shipping volume weight 27,9 kg

Product information


GTIN/EAN number 404576 1235 144

Trade number 90160010

REACH classification no prohibited substances

Pictograms

STANDARD



OPTION



FACTORY

