PROFESSIONAL MEASURING
SINCE 1844

KERN


Product brochure

31.10.2026

KERN DS 150K1

Precision industrial scale with laboratory accuracy, ideal for the diverse possibilities of Industry 4.0 applications

ENGLISH



CONTACT

KERN & SOHN GmbH
Ziegelei 1
72336 Balingen
Germany

+49 7433 9933-0
info@kern-sohn.com
www.kern-sohn.com

APPLICATION EXAMPLE





ENGLISH

FEATURES

- High-capacity precision balance, ideal for high volume or heavy samples to be weighed with a high degree of accuracy
- User guidance step by step on display by Yes/No dialogue
- Numerical subtraction of tare weight for known container weight. Useful for checking fill-levels
- Precise counting: The automatic reference weight optimisation of reference weight gradually improves the average piece weight value
- Freely programmable weighing unit, e.g. display direct in special units such as length of wire g/m, surface weight g/m^2, or else
- KERN Universal Port (KUP): permits the connection of an external KUP interface adapter, such as, for example, RS-232, USB, Bluetooth, WiFi or Ethernet, for the exchange of data and control commands, without any installation outlay
- KERN Communication Protocol (KCP): The KCP permits searching and remote control of the balance using external control devices or computers
- Standardised, simplified concept of operation
- Protective working cover included with delivery

TECHNICAL DATA

- Large backlit LCD display, digit height 21 mm
- Weighing platform dimensions, stainless steel, W×D×H 500×400×127 mm
- Dimensions of display device W×D×H 225×115×60 mm
- Cable length of display device approx. 2,5 m
- Net weight approx. 12 kg
- Permissible ambient temperature -10 °C/40 °C

MAIN SCOPE OF APPLICATIONS

- Quality assurance
- Test equipment monitoring
- Digital processes

PICTOGRAMS

Standard



Option



MODEL OVERVIEW

Model	Weighing capacity [Max]	Readability [d]	Dimensions weighing surface	Net weight approx.
DS 30K0.1L	30 kg	0,0001 kg	500×400 mm	12 kg
DS 36K0.2L	36 kg	0,0002 kg	500×400 mm	12 kg
DS 60K0.2	60 kg	0,0002 kg	500×400 mm	12 kg
DS 65K0.5	65 kg	0,0005 kg	500×400 mm	12 kg
DS 100K0.5	100 kg	0,0005 kg	500×400 mm	12 kg
DS 150K1	150 kg	0,001 kg	500×400 mm	12 kg

ACCESSORIES

Model	Description
CFS-A03	Signal lamp KERN CFS-A03
DE-A12	Protective working cover DE-A12
DS-A04	Tripod DS-A04, Height of stand approx. 330 mm
DS-A05	Tripod DS-A05, Height of stand approx. 600 mm
KUP-01	RS-232 interface KUP-01
KUP-03	Interface USB-Device KUP-03
KUP-04	Ethernet interface KUP-04
KUP-05	WiFi interface KUP-05
KUP-06	Bluetooth BLE interface KUP-06
KUP-13	Extension box KUP-13
YGR-01	ESD grounding plug incl. grounding cable YGR-01
YKA-27	Power adapter YKA-27 (5,9V, 1A | 100 V - 240 V, 50 / 60 Hz | EURO, UK, US, CH)

ENGLISH

Model	Description
YKC-01	Thermal printer YKC-01
YKG-01	Dot Matrix Printer YKG-01
YKH-01	Thermal printer YKH-01
YKR-01	Rechargeable battery pack YKR-01
YKT-01	Needle printer YKT-01
YRO-02	roller conveyor YRO-02

SOFTWARE

Model	Description
SCD-4.0-DL	Software SCD-4.0-DL (Scope of supplies: Download link for 1 license)
SCD-4.0-DLS05	Software SCD-4.0-DLS05 (Scope of supplies: Download link for 5 licenses)
SCD-4.0-PRO-DL	Software SCD-4.0-PRO-DL (Scope of supplies: Download link for 1 license)
SCD-4.0-PRO-DL-AS05	Software SCD-4.0-PRO-DL-AS05 (Scope of supplies: Download link for 5 licenses)
SET-01	Software KERN EasyTouch SET-01-2025a Base
SET-01	Software KERN EasyTouch SET-01 Base
SET-04	Software KERN EasyTouch SET-04-2025a Density
SET-04	Software KERN EasyTouch SET-04 Density
SET-05	Software KERN EasyTouch SET-05-2025a Dynamic
SET-05	Software KERN EasyTouch SET-05 Dynamic
SET-06	Software KERN EasyTouch SET-06-2025a Classification
SET-06	Software KERN EasyTouch SET-06 Classification
SET-07	Software KERN EasyTouch SET-07-2025a Variable
SET-07	Software KERN EasyTouch SET-07 Variable
SET-08	Software KERN EasyTouch SET-08-2025a Take-out
SET-08	Software KERN EasyTouch SET-08 Take-out
SET-10	Software KERN EasyTouch SET-10 Save Server
SET-11	Software KERN EasyTouch SET-11-2025a Safety
SET-11	Software KERN EasyTouch SET-11 Safety
SET-14	Software KERN EasyTouch SET-14-2025a Individual Print
SET-14	Software KERN EasyTouch SET-14 Individual Print
SET-16	Software KERN EasyTouch SET-16-2025a Batch and Statistics

Model	Description
SET-16	Software KERN EasyTouch SET-16 Batch and Statistics
SET-17	Software KERN EasyTouch SET-17-2025a PrePack
SET-17	Software KERN EasyTouch SET-17 PrePack
SET-18	Software KERN EasyTouch SET-18-2025a Container Master
SET-18	Software KERN EasyTouch SET-18 Container Master
SET-21	Software KERN EasyTouch SET-21-2025a Formulation
SET-21	Software KERN EasyTouch SET-21 Formulation
SET-22	Software KERN EasyTouch SET-22-2025a Difference
SET-22	Software KERN EasyTouch SET-22 Difference
SET-31	Software KERN EasyTouch SET-31-2025a Tolerance
SET-31	Software KERN EasyTouch SET-31 Tolerance
SET-32	Software KERN EasyTouch SET-32-2025a Count
SET-32	Software KERN EasyTouch SET-32 Count
SET-33	Software KERN EasyTouch SET-33-2025a Target Count
SET-33	Software KERN EasyTouch SET-33 Target Count
SET-35	Software KERN EasyTouch SET-35-2025a Assembly Count
SET-35	Software KERN EasyTouch SET-35 Assembly Count
SET-37	Software KERN EasyTouch SET-37-2025a Export Manager
SET-37	Software KERN EasyTouch SET-37 Export Manager
SET-39	Software KERN EasyTouch SET-39 Data Interface
SET-40	Software KERN EasyTouch SET-40 Protect
SET-46	Software KERN EasyTouch SET-46-2025a Backup Scheduler
SET-46	Software KERN EasyTouch SET-46 Backup Scheduler
SET-51	Software KERN EasyTouch SET-51-2025a Audit Logs
SET-51	Software KERN EasyTouch SET-51 Audit Logs
SET-52	Software KERN EasyTouch SET-52-2025a Inventory
SET-52	Software KERN EasyTouch SET-52 Inventory
SET-261	Software KERN EasyTouch SET-261 Audio Management
SET-311	Software KERN EasyTouch SET-311-2025a Quick Key
SET-311	Software KERN EasyTouch SET-311 Quick Key
SET-411	Software KERN EasyTouch SET-411-2025a Hotkeys

Model	Description
SET-411	Software KERN EasyTouch SET-411 Hotkeys

SERVICES

Model	Description
963-129	DAkkS calibration certificate 963-129
969-517	Confirmation of the manufacturer's specification (only in combination with DAkkS calibration certificate)969-517
970-105	Warranty extension (+2 years) 970-105

KERN Pictogram Overview

	External adjustment: Adjusting accuracy using external adjustment weight
	KERN IoT-Line balances – smart weighing solutions for the digital future
	KERN Universal Port (KUP): allows the connection of external KUP interface adapters, e.g. RS-232, RS-485, USB, Bluetooth, WiFi, Analogue, Ethernet etc. for the exchange of data and control commands, without installation effort
	KERN Communication Protocol (KCP): a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems
	Piece counting: Reference quantities selectable. Display can be switched from piece to weight
	Sum function: The weight values of weighed items can be added together and the total printed out
	Percentage determination: determining the deviation in % from the target value (100 %)
	Units can be switched to e.g. non-metric units
	Measuring with tolerance range (checkweighing): Upper and lower limit values can be programmed, e.g. for sorting, portioning or for measuring coatings or material thicknesses. The process is supported by an acoustic and/or optical signal
	Hold function: When the weighing conditions are unstable, a stable weight is calculated as an average value
	Universal plug-in power supply: With universal input and optional input socket adapters for EU, CH, GB or EU, CH, GB, US or EU, CH, GB, US, AUS
	Weighing principle Strain gauges: Electrical resistor on an elastic deforming body
	Package shipment by courier service: The duration of internal product provision is one day
	EasyTouch: Suitable for the connection, data transmission and control through PC or tablet
	Data interface RS-232: For connection to printers, PCs or other peripheral devices for data transfer over longer distances. Network in bus topology possible
	Data Interface USB: For connection to printers, PCs or other peripheral devices
	Data interface Bluetooth: For connection to printers, PCs or other peripheral devices
	Data interface WiFi: For data transfer to printers, PCs or other peripheral devices
	Network interface: For connecting the measuring device to an Ethernet network
	Rechargeable battery pack: Rechargeable set
	Accredited calibration (DKD): The duration of the accredited calibration is 3 working days

ENGLISH