PROFESSIONAL MEASURING
SINCE 1844

KERN

Product brochure

30.10.2026

KERN FGE 10K-3

Precise design kitchen scale for kitchen, cafetaria, gastronomy

ENGLISH



CONTACT

KERN & SOHN GmbH
Ziegelei 1
72336 Balingen
Germany

+49 7433 9933-0
info@kern-sohn.com
www.kern-sohn.com







ENGLISH

FEATURES

- Weighing plate made out of safety glass
- Easy and hygienic cleaning
- Low overall height for secure footing and space-saving storage
- Secure and non-slip positioning with rubber feet
- Very easy to use 1 Button
- Comfortable taring with just one keystroke. For example, you can tare a bowl before starting a formulation. In addition, you can tare each time you weigh in a formulation ingredient, so that you can weigh in the next formulation ingredient with the weight indicated in the formula without having to do any calculations
- Integrated AUTO-OFF function to preserve the batteries
- Large high-contrasted display that is easy to read
- Delivered in single design packaging

TECHNICAL DATA

- Large backlit LED segments display, digit height 22 mm
- Dimensions weighing surface, glass, W×D 272×205 mm
- Ready for use: Batteries included, 3×1.5 V AAA, operating time up to 25 h
- Overall dimensions 272×250×22 mm
- Net weight approx. 0,50 kg

MAIN SCOPE OF APPLICATIONS

- Leisure and hobby activities
- Gastronomy
- Dietetics
- educational institutions
- Food industry

PICTOGRAMS

Standard



Option



MODEL OVERVIEW

Model	Weighing capacity [Max]	Readability [d]	Dimensions weighing surface
FGE 5K-3	5000 g	1 g	152×230 mm
FGE 5K-3S05	5000 g	1 g	152×230 mm
FGE 10K-3	15000 g	1 g	272×205 mm
FGE 10K-3S05	15000 g	1 g	272×205 mm

ENGLISH

ACCESSORIES

Model	Description
969-517	Confirmation of the manufacturer's specification (only in combination with DAkkS calibration certificate)969-517

SERVICES

Model	Description
961-248	Adjustment at the location of installation 961-248 (Not in combination with verification)
963-128	DAkkS calibration certificate 963-128
969-517	Confirmation of the manufacturer's specification (only in combination with DAkkS calibration certificate)969-517
970-011	Warranty extension (+3 years) 970-011

KERN Pictogram Overview

	External adjustment: Adjusting accuracy using external adjustment weight
	Units can be switched to e.g. non-metric units
	Battery operation: Ready for battery operation
	Weighing principle Strain gauges: Electrical resistor on an elastic deforming body
	Package shipment by courier service: The duration of internal product provision is one day
	Accredited calibration (DKD): The duration of the accredited calibration is 3 working days

ENGLISH