PROFESSIONAL MEASURING
SINCE 1844

KERN

Product brochure

30.10.2026

KERN FGE 5K-3S05

Precise design kitchen scale for kitchen, cafetaria, gastronomy

ENGLISH



CONTACT

KERN & SOHN GmbH
Ziegelei 1
72336 Balingen
Germany

+49 7433 9933-0
info@kern-sohn.com
www.kern-sohn.com







ENGLISH

FEATURES

- Easy and hygienic cleaning
- Low overall height for secure footing and space-saving storage
- Secure and non-slip positioning with rubber feet
- Very easy to use: 2 Buttons
- Comfortable taring with just one keystroke. For example, you can tare a bowl before starting a formulation. In addition, you can tare each time you weigh in a formulation ingredient, so that you can weigh in the next formulation ingredient with the weight indicated in the formula without having to do any calculations
- Integrated AUTO-OFF function to preserve the batteries
- Large high-contrasted display that is easy to read
- Delivered in single design packaging

TECHNICAL DATA

- Large backlit LCD display, digit height 18 mm
- Dimensions weighing surface, acryl, W×D 152×230 mm
- Ready for use: Batteries included, 2×CR2032, operating time up to 13 h
- Overall dimensions 152×230×15 mm
- Net weight approx. 1,8 kg

MAIN SCOPE OF APPLICATIONS

- Leisure and hobby activities
- Gastronomy
- Dietetics
- educational institutions
- Food industry

PLEASE NOTE FOR YOUR ORDER

- The models are delivered in a set of 5 units. That means the price refers to a delivery of 5 units

PICTOGRAMS

Standard



Option



MODEL OVERVIEW

Model	Weighing capacity [Max]	Readability [d]	Dimensions weighing surface
FGE 5K-3	5000 g	1 g	152×230 mm
FGE 5K-3S05	5000 g	1 g	152×230 mm
FGE 10K-3	15000 g	1 g	272×205 mm
FGE 10K-3S05	15000 g	1 g	272×205 mm

ENGLISH

ACCESSORIES

Model	Description
346-76	Test weight 346-76 (OIML Class M1, Nominal value 5 kg, Block Eco, cast iron lacquered)

SERVICES

Model	Description
961-247S05	Adjustment at the location of installation (set of 5 units) 961-247S05 (Not in combination with verification)
963-127S05	DAkkS calibration certificate (set of 5 units) 963-127S05
969-517	Confirmation of the manufacturer’s specification (only in combination with DAkkS calibration certificate)969-517
970-012	Warranty extension (+2 years) 970-012

KERN Pictogram Overview

	External adjustment: Adjusting accuracy using external adjustment weight
	Units can be switched to e.g. non-metric units
	Battery operation: Ready for battery operation
	Weighing principle Strain gauges: Electrical resistor on an elastic deforming body
	Package shipment by courier service: The duration of internal product provision is one day
	Accredited calibration (DKD): The duration of the accredited calibration is 3 working days

ENGLISH