



Discover more details and matching accessories online!

High resolution bench scale with large weighing range and robust stainless steel weighing plate

Features

- Thanks to the high resolution of up to 360.000 points it is ideal for high-precision weighing in the industrial field
- Robust plastic die-cast housing: maintains the stability, protects the weighing technology elements and is robust enough to cope with everyday use
- KERN Universal Port (KUP): permits the connection of an external KUP interface adapter, such as, for example, RS-232, USB, Bluetooth, WiFi or Ethernet, for the exchange of data and control commands, without any installation outlay

- KERN Communication Protocol (KCP): The KCP permits searching and remote control of the balance using external control devices or computers
- PRE-TARE function for manual subtraction of a known container weight, useful for checking fill-levels
- Freely programmable weighing unit, e.g. display direct in special units such as length of wire g/m, surface weight g/m², or else
- Level indicator and levelling feet for precise levelling of the scale, fitted as standard
- Protective working cover included with delivery

Technical data

- Large backlit LCD display, digit height 25 mm
- Dimensions weighing surface, stainless steel, W×D 340×240 mm
- Overall dimensions W×D×H, 350×390×120 mm
- Optional battery operation, 4×1.5 V AA not included in scope of delivery, operating time up to 20 h
- Net weight approx. 7 kg
- Permissible ambient temperature -10 °C/40 °C

STANDARD



OPTION



Model	Weighing capacity [Max] kg	Readability [d] g	Reproducibility g	Linearity g	Smallest part weight (Normal) g/piece	Resolution Points	Options
							Calibr. Certificate DAkkS accr. KERN
FKB 6K0.02	6	0,02	0,04	± 0,1	0,2	300.000	963-128
FKB 8K0.05	8	0,05	0,05	± 0,15	0,5	160.000	963-128
FKB 16K0.05	16	0,05	0,1	± 0,25	0,5	320.000	963-128
FKB 8K0.1	8	0,1	0,1	± 0,3	1	80.000	963-128
FKB 16K0.1	16	0,1	0,1	± 0,3	1	160.000	963-128
FKB 15K0.5	15	0,5	0,5	± 1,5	10	30.000	963-128
FKB 36K0.1	36	0,1	0,2	± 0,5	1	360.000	963-128
FKB 36K0.2	36	0,2	0,4	± 1	2	180.000	963-128
FKB 65K0.2	65	0,2	0,4	± 1	2	325.000	963-129
FKB 30K1	30	1	1	± 3	20	30.000	963-128
FKB 65K1	65	1	1	± 3	20	65.000	963-129