PROFESSIONAL MEASURING
SINCE 1844

KERN

Product brochure

31.10.2026

KERN FPB 6K-3M

Robust bench scale with IP68/IP69K protection and checkweighing display, with optional verification

ENGLISH




CONTACT

KERN & SOHN GmbH
Ziegelei 1
72336 Balingen
Germany

+49 7433 9933-0
info@kern-sohn.com
www.kern-sohn.com







APPLICATION EXAMPLE





ENGLISH

FEATURES

- Dust and splash water protection type IP68/IP69K. Therefore very robust and durable. Ideal for rough environmental conditions
- Stainless steel weighing plate, which makes cleaning easy and hygienic
- Rechargeable battery pack and power supply included with delivery for continuous operation of the scale, even during charging
- Thanks to rechargeable battery operation, compact, lightweight construction, it is suitable for the use in several locations
- Innovative weighing with tolerance range: The colour of the display changes depending on the weight (too light/ok/too heavy) and is an aid to help with portioning, dosing and grading
- Integrated piece-counting function with storable piece weight
- Sleep function: The scale automatically switches to energy-saving mode after an adjustable period of inactivity

TECHNICAL DATA

- Large backlit LCD display, digit height 25 mm
- Dimensions weighing surface, stainless steel, W×D 190×230 mm
- Overall dimensions W×D×H 288×233×102 mm
- Net weight approx. 2,2 kg
- Internal rechargeable battery pack, operating time up to 500 h without backlight, charging time approx. 4 h
- Permissible ambient temperature -10 °C/40 °C

MAIN SCOPE OF APPLICATIONS

- Food industry
- Hygiene
- Packaging industry
- Laboratory applications
- Chemical industry
- Pharmaceutical industry

PLEASE NOTE FOR YOUR ORDER

- For devices that require verification (conformity assessment according to NAWI 2014/31/EU), please include the verification when placing your order, the initial verification is not possible after delivery. Please inform the full address of the location of use for the initial verification

PICTOGRAMS

Standard



Option



Factory



MODEL OVERVIEW

Model	Weighing capacity [Max]	Readability [d]	Reproducibility	Linearity	Dimensions weighing surface
FPB 15K-3	15 kg	0,001 kg	0,001 kg	± 0,003 kg	190×230 mm
FPB 15K-3M	15 kg	0,005 kg	0,005 kg	± 0,015 kg	190×230 mm
FPB 30K-2M	30 kg	0,01 kg	0,01 kg	± 0,03 kg	190×230 mm
FPB 30K-3	30 kg	0,002 kg	0,002 kg	± 0,006 kg	190×230 mm
FPB 3K-3M	3000 g	1 g	1 g	± 3 g	190×230 mm
FPB 3K-4	3000 g	0,2 g	0,2 g	± 0,6 g	190×230 mm
FPB 6K-3	6000 g	0,5 g	0,5 g	± 1,5 g	190×230 mm
FPB 6K-3M	6000 g	2 g	2 g	± 6 g	190×230 mm

ACCESSORIES

Model	Description
YKR-07-A	Rechargeable battery pack YKR-07-A (Li-Ion, 3,7 V, 4.000 mAh)

SERVICES

Model	Description
961-248	Adjustment at the location of installation 961-248 (Not in combination with verification)
963-128	DAkkS calibration certificate 963-128
965-228	Verification / Conformity assessment according to NAWI (2014/31/EU) 965-228
969-517	Confirmation of the manufacturer's specification (only in combination with DAkkS calibration certificate)969-517
970-014	Warranty extension (+3 years) 970-014

KERN Pictogram Overview

	External adjustment: Adjusting accuracy using external adjustment weight
	Piece counting: Reference quantities selectable. Display can be switched from piece to weight
	Units can be switched to e.g. non-metric units
	Measuring with tolerance range (checkweighing): Upper and lower limit values can be programmed, e.g. for sorting, portioning or for measuring coatings or material thicknesses. The process is supported by an acoustic and/or optical signal
	Protection against dust and water splashes IP68
	Protection against dust and water splashes IP69K
	Rechargeable battery pack: Rechargeable set
	Plug-in power supply: 230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available
	Weighing principle Strain gauges: Electrical resistor on an elastic deforming body
	Package shipment by courier service: The duration of internal product provision is one day
	Accredited calibration (DKD): The duration of the accredited calibration is 3 working days
	Conformity assessment: The duration of the conformity assessment is 3 working days

ENGLISH