PROFESSIONAL MEASURING
SINCE 1844

KERN

Product brochure

31.10.2026

KERN IXC 60K-3L

Convenience for industry: Stainless steel platform scales with up to four interfaces and intuitive operation

ENGLISH



CONTACT

KERN & SOHN GmbH
Ziegelei 1
72336 Balingen
Germany

+49 7433 9933-0
info@kern-sohn.com
www.kern-sohn.com

FEATURES

- Tough industry standard suitable for use in harsh industrial applications
- Standardised, convenient KERN concept of operation, consistency across products in terms of design, menu structure, button functions, interface connection and interface protocol
- Industry 4.0: The exchange of data and control commands is optional using up to four interfaces to suit individual requirements: two wired connections (RS-232, Ethernet, USB or analogue module) and two wireless connections (WiFi, Bluetooth)
- Each interface can be set up separately, e.g.:
  - Interface 1 (WiFi): Continuous sending to a PC for documentation of a process
  - Interface 2 (RS-232): Print stable weight
  - Interface 3 (analogue module): Controlling a device when the target weight is reached
  - Interface 4 (Bluetooth): Continuous sending to a tablet to monitor a process
- Available as an option with alibi memory for paperless archiving of weighing results. This also means the results of weighings with mandatory verification can be electronically evaluated and processed further
- Data query and remote control of the balance using a computer or CRM/ERP systems using the KERN Communication Protocol
- Platform: weighing plate of stainless steel, painted steel base, silicone-coated aluminium load cell with protection against dust and water splashes IP65
- Display device: stainless steel, protection against dust and water splashesIP68. Superior display size: digit height 48 mm, bright backlight for easy reading of weighing results, even in poor lighting conditions, integrated power supply

TECHNICAL DATA

- Large backlit LCD display, digit height 48 mm
- Weighing platform dimensions, stainless steel, W×D×H 500×400×127 mm
- Dimensions of display device W×D×H 232×150×77,3 mm
- Cable length of display device approx. 3 m
- Net weight approx. 11 kg
- Permissible ambient temperature -10 °C/40 °C

MAIN SCOPE OF APPLICATIONS

- Process monitoring
- Testing applications
- Production and manufacturing
- Warehouse logistics

PLEASE NOTE FOR YOUR ORDER

- Option: Rechargeable battery pack KERN YKR-01, Option, must be ordered at time of purchase

PICTOGRAMS

Standard



Option



Factory



MODEL OVERVIEW

Model	Weighing capacity [Max]	Readability [d]	Verification value [e]	Minimal load [Min]	Dimensions weighing surface	Net weight approx.
IXC 6K-3M	3 kg; 6 kg	0,001 kg; 0,002 kg	0,001 kg; 0,002 kg	0,02 kg; 0,04 kg	300×240 mm	6 kg
IXC 6K-4	6 kg	0,0002 kg			300×240 mm	6 kg
IXC 10K-3LM	6 kg; 15 kg	0,002 kg; 0,005 kg	0,002 kg; 0,005 kg	0,04 kg; 0,1 kg	400×300 mm	7 kg
IXC 10K-3M	6 kg; 15 kg	0,002 kg; 0,005 kg	0,002 kg; 0,005 kg	0,04 kg; 0,1 kg	300×240 mm	6 kg
IXC 10K-4	15 kg	0,0005 kg			300×240 mm	6 kg
IXC 10K-4L	15 kg	0,0005 kg			400×300 mm	7 kg
IXC 30K-3LM	15 kg; 30 kg	0,005 kg; 0,01 kg	0,005 kg; 0,01 kg	0,1 kg; 0,2 kg	500×400 mm	11 kg
IXC 30K-3M	15 kg; 30 kg	0,005 kg; 0,01 kg	0,005 kg; 0,01 kg	0,1 kg; 0,2 kg	400×300 mm	7 kg
IXC 30K-3	30 kg	0,001 kg			400×300 mm	8 kg
IXC 30K-3L	30 kg	0,001 kg			500×400 mm	11 kg
IXC 60K-2LM	30 kg; 60 kg	0,01 kg; 0,02 kg	0,01 kg; 0,02 kg	0,2 kg; 0,4 kg	500×400 mm	11 kg
IXC 60K-2M	30 kg; 60 kg	0,01 kg; 0,02 kg	0,01 kg; 0,02 kg	0,2 kg; 0,4 kg	400×300 mm	7 kg
IXC 60K-3	60 kg	0,002 kg			400×300 mm	7 kg
IXC 60K-3L	60 kg	0,002 kg			500×400 mm	11 kg
IXC 100K-2LM	60 kg; 150 kg	0,02 kg; 0,05 kg	0,02 kg; 0,05 kg	0,4 kg; 1 kg	650×500 mm	18 kg
IXC 100K-2M	60 kg; 150 kg	0,02 kg; 0,05 kg	0,02 kg; 0,05 kg	0,4 kg; 1 kg	500×400 mm	11 kg
IXC 100K-3	150 kg	0,005 kg			500×400 mm	11 kg
IXC 100K-3L	150 kg	0,005 kg			650×500 mm	19 kg

ENGLISH

Model	Weighing capacity [Max]	Readability [d]	Verification value [e]	Minimal load [Min]	Dimensions weighing surface	Net weight approx.
IXC 300K-2M	150 kg; 300 kg	0,05 kg; 0,1 kg	0,05 kg; 0,1 kg	1 kg; 2 kg	650×500 mm	20 kg
IXC 300K-3	300 kg	0,01 kg			650×500 mm	20 kg

ACCESSORIES

Model	Description
BFS-A07	Tripod BFS-A07, Height of stand approx. 1040 mm
CFS-A03	Signal lamp KERN CFS-A03
IXC-A01	Tripod IXC-A01, Height of stand approx. 330 mm
IXC-A02	Tripod IXC-A02, Height of stand approx. 600 mm
KUM-01	RS-232 interface KUM-01
KUM-03	Interface USB-Device KUM-03
KUM-04	Ethernet interface KUM-04
KUM-05	WiFi interface KUM-05
KUM-06	Bluetooth BLE interface KUM-06
KUM-08	Analogue interface KUM-08
KXS-A07S05	Protective working cover KXS-A07S05, scope of delivery: 5 items
YGR-01	ESD grounding plug incl. grounding cable YGR-01
YKA-01	Schuko> UK Plug Power Adapters YKA-01
YKA-02	Travel adapter YKA-02
YKC-01	Thermal printer YKC-01
YKG-01	Dot Matrix Printer YKG-01
YKH-01	Thermal printer YKH-01
YKR-01	Rechargeable battery pack YKR-01
YKT-01	Needle printer YKT-01
YMM-06	Alibi memory with Real Time Clock YMM-06
YRO-02	roller conveyor YRO-02

ENGLISH

SOFTWARE

Model	Description
SCD-4.0-DL	Software SCD-4.0-DL (Scope of supplies: Download link for 1 license)
SCD-4.0-DLS05	Software SCD-4.0-DLS05 (Scope of supplies: Download link for 5 licenses)
SCD-4.0-PRO-DL	Software SCD-4.0-PRO-DL (Scope of supplies: Download link for 1 license)
SCD-4.0-PRO-DL-AS05	Software SCD-4.0-PRO-DL-AS05 (Scope of supplies: Download link for 5 licenses)
SET-01	Software KERN EasyTouch SET-01-2025a Base
SET-01	Software KERN EasyTouch SET-01 Base
SET-04	Software KERN EasyTouch SET-04-2025a Density
SET-04	Software KERN EasyTouch SET-04 Density
SET-05	Software KERN EasyTouch SET-05-2025a Dynamic
SET-05	Software KERN EasyTouch SET-05 Dynamic
SET-06	Software KERN EasyTouch SET-06-2025a Classification
SET-06	Software KERN EasyTouch SET-06 Classification
SET-07	Software KERN EasyTouch SET-07-2025a Variable
SET-07	Software KERN EasyTouch SET-07 Variable
SET-08	Software KERN EasyTouch SET-08-2025a Take-out
SET-08	Software KERN EasyTouch SET-08 Take-out
SET-10	Software KERN EasyTouch SET-10 Save Server
SET-11	Software KERN EasyTouch SET-11-2025a Safety
SET-11	Software KERN EasyTouch SET-11 Safety
SET-14	Software KERN EasyTouch SET-14-2025a Individual Print
SET-14	Software KERN EasyTouch SET-14 Individual Print
SET-16	Software KERN EasyTouch SET-16-2025a Batch and Statistics
SET-16	Software KERN EasyTouch SET-16 Batch and Statistics
SET-17	Software KERN EasyTouch SET-17-2025a PrePack
SET-17	Software KERN EasyTouch SET-17 PrePack
SET-18	Software KERN EasyTouch SET-18-2025a Container Master
SET-18	Software KERN EasyTouch SET-18 Container Master
SET-21	Software KERN EasyTouch SET-21-2025a Formulation
SET-21	Software KERN EasyTouch SET-21 Formulation
SET-22	Software KERN EasyTouch SET-22-2025a Difference

Model	Description
SET-22	Software KERN EasyTouch SET-22 Difference
SET-31	Software KERN EasyTouch SET-31-2025a Tolerance
SET-31	Software KERN EasyTouch SET-31 Tolerance
SET-32	Software KERN EasyTouch SET-32-2025a Count
SET-32	Software KERN EasyTouch SET-32 Count
SET-33	Software KERN EasyTouch SET-33-2025a Target Count
SET-33	Software KERN EasyTouch SET-33 Target Count
SET-35	Software KERN EasyTouch SET-35-2025a Assembly Count
SET-35	Software KERN EasyTouch SET-35 Assembly Count
SET-37	Software KERN EasyTouch SET-37-2025a Export Manager
SET-37	Software KERN EasyTouch SET-37 Export Manager
SET-39	Software KERN EasyTouch SET-39 Data Interface
SET-40	Software KERN EasyTouch SET-40 Protect
SET-46	Software KERN EasyTouch SET-46-2025a Backup Scheduler
SET-46	Software KERN EasyTouch SET-46 Backup Scheduler
SET-51	Software KERN EasyTouch SET-51-2025a Audit Logs
SET-51	Software KERN EasyTouch SET-51 Audit Logs
SET-52	Software KERN EasyTouch SET-52-2025a Inventory
SET-52	Software KERN EasyTouch SET-52 Inventory
SET-261	Software KERN EasyTouch SET-261 Audio Management
SET-311	Software KERN EasyTouch SET-311-2025a Quick Key
SET-311	Software KERN EasyTouch SET-311 Quick Key
SET-411	Software KERN EasyTouch SET-411-2025a Hotkeys
SET-411	Software KERN EasyTouch SET-411 Hotkeys

SERVICES

Model	Description
961-249	Adjustment at the location of installation 961-249 (Not in combination with verification)
963-129	DAkkS calibration certificate 963-129
965-403	Cable extension 965-403 (< 4 m)
965-404	Cable extension 965-404 (4–7 m)

Model	Description
965-405	Cable extension 965-405 (7–20 m)
969-517	Confirmation of the manufacturer's specification (only in combination with DAkkS calibration certificate)969-517
970-104	Warranty extension (+2 years) 970-104
970-105	Warranty extension (+2 years) 970-105

KERN Pictogram Overview

	External adjustment: Adjusting accuracy using external adjustment weight
	KERN IoT-Line balances – smart weighing solutions for the digital future
	KERN Communication Protocol (KCP): a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems
	Piece counting: Reference quantities selectable. Display can be switched from piece to weight
	Sum function: The weight values of weighed items can be added together and the total printed out
	Percentage determination: determining the deviation in % from the target value (100 %)
	Measuring with tolerance range (checkweighing): Upper and lower limit values can be programmed, e.g. for sorting, portioning or for measuring coatings or material thicknesses. The process is supported by an acoustic and/or optical signal
	Hold function: When the weighing conditions are unstable, a stable weight is calculated as an average value
	Load Cell: Protection against dust and water splashes IP65
	Protection against dust and water splashes IP68
	Integrated power supply unit: Integrated in device. 230 V/50 Hz standard EU. More standards e.g. GB, USA or AUS on request
	Weighing principle Strain gauges: Electrical resistor on an elastic deforming body
	Package shipment by courier service: The duration of internal product provision is one day
	EasyTouch: Suitable for the connection, data transmission and control through PC or tablet
	Accredited calibration (DKD): The duration of the accredited calibration is 3 working days
	Alibi memory: Secure, electronic archiving of measuring results, complying with the 2014/31/EU standard
	Data interface RS-232: For connection to printers, PCs or other peripheral devices for data transfer over longer distances. Network in bus topology possible
	Data Interface USB: For connection to printers, PCs or other peripheral devices
	Data interface Bluetooth: For connection to printers, PCs or other peripheral devices
	Analogue interface: to connect a suitable peripheral device for analogue processing of the measurements
	Network interface: For connecting the measuring device to an Ethernet network
	GLP/ISO protocol: The measuring device generates a GLP-compliant printout
	Value & time: The measuring device displays the value, date, and time, regardless of the connected printer

ENGLISH



Rechargeable battery pack: Rechargeable set