PROFESSIONAL MEASURING
SINCE 1844

KERN

Product brochure

31.10.2026

KERN KFD 1500V40M

Weighing bridge made from stainless steel, two integrated access ramps, extremely resistant to bending

ENGLISH



CONTACT

KERN & SOHN GmbH
Ziegelei 1
72336 Balingen
Germany

+49 7433 9933-0
info@kern-sohn.com
www.kern-sohn.com

FEATURES

- Weighing bridge made from stainless steel, two integrated access ramps, extremely resistant to bending
- Extremely flat construction to facilitate access: access height only 45 mm
- 4 Load cells, stainless steel, encapsulated, IP68, OIML R60 approval for verification, Class III, 3000 e

TECHNICAL DATA

- Weighing platform dimensions W×D×H 1600×1220×95 mm, stainless steel
- Connection cable approx. 5 m
- Net weight approx. 130 kg

PICTOGRAMS

Standard



Factory



MODEL OVERVIEW

Model	Weighing capacity [Max]	Readability [d]	Verification value [e]	Minimal load [Min]	Cable length	Dimensions weighing surface	Net weight approx.
KFD 600V40M	600 kg	200 g	200 g	4 kg	5 m	1000×1000 mm	130 kg
KFD 1500V40M	1500 kg	500 g	500 g	10 kg	5 m	1000×1000 mm	130 kg

ACCESSORIES

Model	Description
BFN-A03	Pair of base plates BFN-A03

SERVICES

Model	Description
963-130	DAkkS calibration certificate 963-130
965-230	Verification / Conformity assessment according to NAWI (2014/31/EU) 965-230
965-413	Assembly of components 965-413 (> 350 kg – 1500 kg)

ENGLISH

Model	Description
970-113	Warranty extension (+2 years) 970-113

KERN Pictogram Overview

PT IP 67	Platform: Protection against dust and water splashes IP67
LC IP 68	Load Cell: Protection against dust and water splashes IP68
2 DAYS	Pallet shipment: The duration of internal product provision are two days
M	Conformity assessment: The duration of the conformity assessment is 3 working days