PROFESSIONAL MEASURING
SINCE 1844

KERN

Product brochure

31.10.2026

KERN KFP 150V40M

Platform: entirely out of stainless steel

ENGLISH



CONTACT

KERN & SOHN GmbH
Ziegelei 1
72336 Balingen
Germany

+49 7433 9933-0
info@kern-sohn.com
www.kern-sohn.com

FEATURES

- Platform: entirely out of stainless steel
- 1 load cell, stainless steel, encapsulated, IP68, OIML R60 approval for verification, class III, 3000 e
- Level indicator and levelling feet for accurate levelling of the balance

TECHNICAL DATA

- Weighing platform dimensions W×D×H 500×400×126 mm, stainless steel
- Connection cable approx. 3 m
- Net weight approx. 12 kg

PICTOGRAMS

Standard



Factory



MODEL OVERVIEW

Model	Weighing capacity [Max]	Readability [d]	Verification value [e]	Minimal load [Min]	Cable length	Dimensions weighing surface	Net weight approx.
KFP 6V40M	6 kg	500 mg	1 g; 2 g	20 g	3 m	300×240 mm	7 kg
KFP 15V40LM	15 kg	1 g	2 g; 5 g	40 g	3 m	400×300 mm	7 kg
KFP 15V40M	15 kg	1 g	2 g; 5 g	40 g	3 m	300×240 mm	4,8 kg
KFP 30V40LM	30 kg	2 g	5 g; 10 g	100 g	3 m	500×400 mm	11 kg
KFP 30V40M	30 kg	2 g	5 g; 10 g	100 g	3 m	400×300 mm	8 kg
KFP 60V40LM	60 kg	5 g	10 g; 20 g	200 g	3 m	500×400 mm	11 kg
KFP 60V40M	60 kg	5 g	10 g; 20 g	200 g	3 m	400×300 mm	10 kg
KFP 150V40LM	150 kg	10 g	20 g; 50 g	400 g	3 m	650×500 mm	20 kg
KFP 150V40M	150 kg	10 g	20 g; 50 g	400 g	3 m	500×400 mm	12 kg
KFP 300V40M	300 kg	20 g	50 g; 100 g	1 kg; 2 kg	3 m	650×500 mm	20 kg

ENGLISH

SERVICES

Model	Description
963-129	DAkkS calibration certificate 963-129
965-229	Verification / Conformity assessment according to NAWI (2014/31/EU) 965-229
965-412	Assembly of components 965-412 (> 50 kg - 350 kg)
970-104	Warranty extension (+2 years) 970-104

KERN Pictogram Overview

LC IP 68	Load Cell: Protection against dust and water splashes IP68
1 DAY	Package shipment by courier service: The duration of internal product provision is one day
M	Conformity assessment: The duration of the conformity assessment is 3 working days