

KERN KFP 150V40M

Platform: entirely out of stainless steel



Category

| | |
|------------------|--------------|
| Brand | KERN |
| Product category | Component |
| Product group | Platform |
| Product family | KFP-V40-IP68 |

Measuring System

| | |
|-------------------------------------|-----------------------------------|
| Weighing capacity [Max] | 150 kg |
| Readability [d] | 10 g |
| Minimum weight [Min] | 400 g |
| Loadcell type | stainless steel IP68 encapsulated |
| Load cell connection | 6-wire |
| Load cell OIML class | C3 |
| Load cell - Resolution (verifiable) | 2 × 3000 e |

Construction

| | |
|---|------------------|
| Dimensions weighing surface (W×D) | 500×400 mm |
| Dimensions weighing surface | 500×400 mm |
| Dimensions weighing platform (W×D×H) | 500×400×126 mm |
| Material weighing plate | stainless steel |
| Material platform | Stainless steel |
| Material load cell(s) | Stainless steels |
| Levelling feet adjustable | ✓ |
| Cable length | 3 m |
| Allowed cable length display device [Max] | 20 m |
| Platform Construction | Single-Cell |
| Load cells - number | 1 |

Functions

| | |
|---------------------------|------------------|
| IP protection - platform | no IP protection |
| IP protection - load cell | IP68 |

Approval

| | |
|---|------------|
| Conformity assessment possible ex works | ✓ |
| Verification scale interval [e] | 20 g; 50 g |

Services (optional)

| | |
|--|---------|
| Article number for conformity assessment | 965-229 |
| Article number for DAkkS calibration | 963-129 |

Packing & Shipping

| | |
|------------------------------|----------------|
| Delivery time | 1 d |
| Dimensions packaging (W×D×H) | 930×555×225 mm |
| Shipping method | Parcel service |
| Net weight approx. | 12 kg |
| Gross weight approx. | 15 kg |
| Shipping weight | 23,2 kg |

Pictograms

STANDARD



FACTORY

