

# KERN MCN 200K-1M

Mobile integratable chair scale for wireless transfer of weighing data to EMR or EHR systems



Conformity assessment possible ex works	✓
Accuracy classe	III
Verification scale interval [e]	0,1 kg

Display	
Display type	LCD
Display type	LCD
Display backlight	no
Display screen size	100×40 mm
Display segments	6
Display digit height	25 mm
Languages of the user interface	Symbol language

Construction	
Dimension display device (W×D×H)	210×54×100 mm
Dimensions weighing platform (W×D×H)	435×380×515 mm
Dimensions completely mounted (W×D×H)	625×979×956 mm
Material display housing	Plastics
Material housing	ABS plastic
Material weighing plate	plastic
Material platform	steel, varnished
Dimensions weighing surface (W×D)	390×360 mm
Cable length	1,8 m
Display device cable length	1,8 m
Material load cell(s)	aluminium
Levelling feet adjustable	✓
Level indicator	✓
Transport wheels	✓

Functions	
Alibi memory	optional internal memory
Alibi memory - number of memory spaces	250.000
Function for BMI calculation	✓
Hold function	✓
IP protection - complete device	-
IP protection - display	no IP protection
IP protection - platform	IP65
IP protection - load cell	IP65
Auto-off interval(s) in battery mode/rechargeable battery mode	off selectable 3, 5, 15, 30 min

Category	
Brand	KERN
Product category	Medical scale
Product group	Chair scale
Product family	MCN

Measuring System	
Weighing system	Strain gauge
Weighing capacity [Max]	250 kg
Units (if device is conformity assessed)	kg
Readability [d]	0,1 kg
Resolution	2.500
Linearity	± 0,1 kg
Reproducibility	0,1 kg
Tare range	250 kg
Units	kg
Minimum weight [Min]	2 kg
Adjustment options	Adjusting with external weight
Recommended adjusting weight	250 kg (M1)
Stabilization time	3 s
Warm-up time	10 min
Eccentric loading at 1/3 [Max]	0,1 kg
Loadcell type	DMS
Default unit	kg
Conformity assessment possible	✓
Construction type of the scale	Single-range balance

Approval	
CE mark	✓

# KERN MCN 200K-1M

# KERN

Mobile integratable chair scale for wireless transfer of weighing data to EMR or EHR systems

Auto-off interval(s) in mains power mode	off selectable 3, 5, 15, 30 min
Tare function	manual (single & multi)
Number of keys for operation	6

## Power Supply

Supplied power supply	Power supply & battery function (battery not included)
Plug-in power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO UK
Input voltage power supply / power [Max]	100 V - 240 V, 50 / 60 Hz
Input voltage device / power [Max]	6 V, 1 A
Battery / accumulator type	Alkali(-Manganese) Li-Ion
Battery	6×1.5 V AA
Battery connection	Battery insert
Battery operating time	20 h
Rechargeable battery operating time - backlight off	48 h
Rechargeable battery charging time	8 h
Rechargeable battery optional	Rchrg. battery optional

## Environmental conditions

Ambient temperature [Min]	10 °C
Ambient temperature [Max]	40 °C
Humidity of environment [Min]	5 %
Humidity of environment [Max]	80 %
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

## Packing & Shipping

Delivery time	2 d
Dimensions packaging (W×D×H)	1080×690×1080 mm
Net weight	23,3 kg
Shipping method	Freight
Net weight approx.	24 kg
Gross weight approx.	36 kg
Shipping weight	161 kg

## Services (optional)

Article number for adjustment at the location of installation	961-249
---	---------

Article number for conformity assessment	965-129
Article number for DAkkS calibration	963-129
Article number for certificate of conformity (verification)	969-517

## Interface

Interfaces	RS-232 (optional) Bluetooth (optional) WiFi standard Alibi memory (optional, factory) USB-Device (optional) KUP
EasyTouch (ET) - Compatibility	vollständig

## Pictograms

### STANDARD



### OPTION



### FACTORY

