



## Material thickness gauge for ultrasonic material thickness testing in Echo-Echo principle

### Features

- Dual measuring modes to determine material thickness:
  - Pulse-Echo mode (up to 600 mm)
  - Echo-Echo mode (up to 100 mm)
- Echo-Echo measurement: Determines the actual material thickness regardless of whether there is a coating on the base metal. In this way, the wall thickness of pipes, for example, can be determined without having to remove the coating. The measurement will be output, with the adjustment for the coating thickness taken into account
- Can be used on these materials, as well as others: Metals, plastics, ceramics, composite materials, epoxy, glass and other materials
- High-precision mode: Readout accuracy can be switched from 0.1 mm to 0.01 mm
- **1** Premium display: TFT colour display (320x240) with adjustable brightness, so that it can be read under the most varied lighting conditions
- Large internal data memory for up to 100 data sets each with 100 individual values
- Energy-saving operation with 2x AA batteries and an operating time of at least 30 hours, adjustable power-off time (sleep mode) and adjustable display switch-off (standby mode)

- **2** USB data output for easy data download from the device memory to the PC, as standard
- Triple-calibration mode: Automatic 0-point adjustment, 1-point adjustment at a specified material thickness, 2-point precision adjustment with two specified material thicknesses
- 3 different measurement modes: standard measuring (single measurement), scan mode (for continuous measurement and display of the ACTUAL value, the MIN and MAX value of the measuring sequence) and DIFF mode with calculation of the difference between the ACTUAL measured value and a manually defined nominal thickness
- Limit alarm function: Upper and lower limit adjustable. The measurement process is supported by an audible and visual signal
- Menu languages: DE, EN, FR, ES, IT
- Date and time can be adjusted. It is possible to store the measurement values with a time stamp
- Standard measuring probe SAUTER ATU-US12 included with delivery
- Scope of delivery: Operating instructions, batteries, external measuring head (∅ 10 mm) and ultrasound contact gel

- **3** Delivered in a robust carrying case
- Interface cable SAUTER FL-A01 (for use of the software) included

### Technical data

- Measuring precision: 0,4 % of [Max] ± 0,04 mm
- Overall dimensions WxDxH 31x69x130 mm
- Battery operation, batteries standard (2x1.5 V AA), AUTO-OFF function to preserve the battery
- Net weight approx. 0,25 kg

### Accessories

- External measuring head, 5 MHz, ∅ 10 mm, for echo-echo measuring, SAUTER ATU-US12
- Ultrasound contact gel, refill pack, approx. 70 ml, SAUTER ATB-US03
- BalanceConnection software for flexible measured value recording or transmission, compatible with Microsoft® Excel, Access and other applications, scope of delivery: 1 CD, 1 license, KERN SCD-4.0
- Other sensors on request
- Further details and plenty of further accessories see [www.kern-sohn.com/de/](http://www.kern-sohn.com/de/)

#### STANDARD



#### OPTION



Model	Measuring range Echo-Echo	Measuring range Pulse-Echo	Readout [d] mm	Sensor	Sound velocity m/sec	Option
						<b>Factory Calibration Certificate</b>
SAUTER TO 100-0.01EE	mm 3 - 100	mm 0,7 - 600	0,01	5 MHz   ∅ 10 mm	200 - 19999	KERN 961-113