KERN **OKO 178C832**

Digital set with metallurgical microscope, camera and C-mount adapter



Date of creation: 25.10.2026

Category	
Brand	Optics
Product category	Microscope
Product group	Digital microscope set
Product family	OKO-S

Construction	
Dimension (W×D×H)	390×235×620 mm
Optical system	Infinity
Tube type	Trinocular
Tube angle of inclination	30°
Tube 360° rotation	✓
Tube type	Siedentopf
Light distribution	0:100 80:20
Contrasting methods	Bright field Polarisation
Standard objectives	5× 10× 20× 50×
Lens quality	Infinity Plan
Nosepiece screw-in locations	5
Interpupillary distance [Min]	50 mm
Interpupillary distance [Max]	75 mm
Diopter adjustment	both-sided
Diopter adjustment [Min]	-5
Diopter adjustment [Max]	5
Colour temperature	5500 K

Functions	
Supported operating systems	Win 7 Win 8 Win 10 Win 11
Camera - Software functions	Image capturing Video capturing Measurements
Camera - Applicable software	Microscope VIS 2.0 Lite (OXM 903)

Interface	
Interfaces	USB 3.0

Ocular	
Ocular field width	HWF
Ocular magnifications	10x
Ocular visual field	22 mm
Ocular diameter	30 mm

Illumination	
Illuminance	Reflected light Transmitted light
Illumination type incident light	LED
Illumination type transmitted light	LED
Illumination intensity incident light	5 W
Illumination intensity transmitted light	5 W
Illumination dimmable	Incident light + Transmitted light, separate
Koehler illumination	✓
Filter possible	✓
Field diaphragm	✓

80000 | Mikroskoptisch	
Bauweise	mechanical
Weg	77 mm; 52 mm
Durchlicht möglich	✓
ATTR_microscopeTableSpecimentHolders	2

Focussing	
Field of view [Min]	0,18 mm
Field of view [Max]	3,6 mm
Torque regulation	✓
Fine drive minimum	0,002 mm

KERN **OKO 178C832**

Digital set with metallurgical microscope, camera and C-mount adapter

Focusing mechanism	coaxial coarse and fine drive

Condensor

Condensor type	Standard
Condenser - Mounting	fixed
Condenser - Aperture	0,3
Aperture diaphragm	✓

Camera

Cameratype	USB3 Microscope camera - C-Mount
Camera - Resolution	5,1 MP
Camera - Sensor type	Aptina CMOS
Camera - Sensor size	1/2,5"
Camera - Colour depth	Colour
Camera - Framerate	14,2 - 101,2 fps
Camera- Mounting types	C-mount
Camera - Exposure method	Rolling Shutter
Camera - Sensor dimensions	5,7×4,28 mm
Camera - Sensor Diagonal	7,13 mm
Camera - Pixel size	2,2×2,2 µm
Camera - Exposure time [Min]	0,1 ms
Camera - Exposure time [Max]	2000 ms

Power Supply

Supplied power supply	Power supply unit
Power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO
Plug-in power supply / adapter for countries - optional	AUS UK US CH
Input voltage power supply / power [Max]	100 - 240 V
Power supply cable removable	removable
Input voltage device / power [Max]	5 V 1000 mA
Power socket for mains adapter	Hollow plug, inside plus, Ø outside 5,5 mm, Ø inside 2,5 mm, long 10 mm

Environmental conditions

Storage temperature [Min]	-5 °C
Storage temperature [Max]	40 °C

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	590×440×390 mm
Shipping method	Parcel service
Net weight approx.	11 kg
Gross weight approx.	14 kg
Shipping weight	20,2 kg
Shipping volume weight	20,2 kg

Product information

GTIN/EAN number	4045761490956
Trade number	90118000
Warranty Time	36 mon
REACH classification	no prohibited substances

Pictograms

STANDARD

