KERN **OZP 933UK**

Predefined stereo microscope sets with PREMIUM universal stand and illumination for your functional workplace, with plug-in power supply for UK



Date of creation: 11.11.2026

Category	
Brand	Optics
Product category	Microscope
Product group	Stereo microscope set
Product family	OZP-9

Construction	
Optical system	Greenough
Tube type	Trinocular
Tube angle of inclination	45°
Tube 360° rotation	✓
Light distribution	50:50
Contrasting methods	Bright field
Interpupillary distance [Min]	54 mm
Interpupillary distance [Max]	76 mm
Diopter adjustment	both-sided
Diopter adjustment [Min]	-5
Diopter adjustment [Max]	5

Ocular	
Ocular type	Eyepiece HSWF 10x / Ø 23mm with anti-fungus, high eye point
Ocular field width	HSWF
Eye point	High Eye Point
Ocular magnifications	10x
Ocular visual field	23 mm
Ocular diameter	30 mm

Objective	
Objectives magnifications	0,65x - 5,5x

Illumination	
Illuminance	Reflected light
Illumination type incident light	LED
Illumination intensity incident light	4,5 W
Illumination dimmable	Incident light

Focussing	
Field of view [Min]	4,2 mm
Field of view [Max]	35,4 mm
Standard total magnification [Min]	6,5x
Standard total magnification [Max]	55x
Click-Stop-Zoom	✓
Zoom [Min]	0,65x
Zoom [Max]	5,5x
Working distance	105 mm
Magnification ratio	8,5:1
Focusing mechanism	coarse drive

Stereomicroscope stand	
Stand type	universal (ball-beared double telescopic arm with plate)
Column height	515 mm
Diameter mounting universal stand (Ø)	37 mm
Diameter mounting microscope head (Ø)	76 mm
Arm length	545 mm

Power Supply	
Supplied power supply	Power supply unit
Power supply type	Built-in power supply
Plug-in power supply / adapter for countries - included with the delivery	UK
Input voltage power supply / power [Max]	100 - 240 V
Input voltage device / power [Max]	100 - 240 V
Power socket for mains adapter	Protective contact plug

Environmental conditions	
Storage temperature [Min]	-5 °C

KERN **OZP 933UK**

Predefined stereo microscope sets with PREMIUM universal stand and illumination for your functional workplace, with plug-in power supply for UK

Storage temperature [Max]	40 °C

Approval

CE mark	✓

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	700×520×350 mm
Shipping method	Parcel service
Net weight approx.	28 kg
Gross weight approx.	32 kg
Shipping weight	30,6 kg
Shipping volume weight	25,5 kg

Product information

GTIN/EAN number	4045761505100
Trade number	90111000
REACH classification	no prohibited substances

Pictograms

STANDARD

