PROFESSIONAL MEASURING
SINCE 1844

KERN

Product brochure

31.10.2026

KERN PBS 6000-2

Multifunctional laboratory balance with single-cell weighing system

ENGLISH



CONTACT

KERN & SOHN GmbH
Ziegelei 1
72336 Balingen
Germany

+49 7433 9933-0
info@kern-sohn.com
www.kern-sohn.com



FEATURES

- CAL adjustment program for adjusting precision, external test weights available separately (see test weights)
- Metal housing: robust and sturdy
- Dosage aid: High stability mode and other filter settings can be selected
- Weighing with tolerance range (checkweighing): a visual signal helps with portioning, dispensing or grading
- Summation of weight values
- Identification number: 4 digits, printed on calibration protocol freely programmable
- Automatic data output to the PC/printer each time the balance is steady
- Protective working cover included with delivery

TECHNICAL DATA

- Large backlit LCD display, digit height 14 mm
- Dimensions weighing surface, stainless steel, W×D 176×189 mm
- Overall dimensions 191×317×79 mm
- Net weight approx. 3,4 kg
- Permissible ambient temperature 10 °C/30 °C

MAIN SCOPE OF APPLICATIONS

- Laboratory applications
- Pharmaceutical applications
- Quality control
- Time-based recording

PICTOGRAMS

Standard



Option



ENGLISH

MODEL OVERVIEW

Model	Weighing capacity [Max]	Readability [d]	Reproducibility	Linearity	Dimensions weighing surface
PBS 600-3	620 g	0,001 g	0,001 g	± 0,002 g	113×110 mm
PBS 1000-3	1020 g	0,001 g	0,001 g	± 0,002 g	113×110 mm
PBS 4000-2	4200 g	0,01 g	0,01 g	± 0,02 g	176×189 mm
PBS 6000-2	6200 g	0,01 g	0,01 g	± 0,02 g	176×189 mm

ACCESSORIES

Model	Description
770-926	RS232 interface cable 770-926
ACS-A01	RS232 interface cable ACS-A01
PBS-A02	Protective working cover PBS-A02
PBS-A02S05	Protective working cover PBS-A02S05, scope of delivery: 5 items
PBS-A03	Density determination set PBS-A03
YKC-01	Thermal printer YKC-01
YKG-01	Dot Matrix Printer YKG-01
YKH-01	Thermal printer YKH-01
YKI-10	RS232-Ethernet adapter YKI-10 (RS-232 standard, Ethernet, RS-485)
YKI-11	RS232-Ethernet adapter YKI-11 (Ethernet, RS-232 standard - 2x)
YKI-12	RS232-WiFi adapter YKI-12
YKT-01	Needle printer YKT-01
YPS-03	Antivibration table YPS-03
YPS-04	Anti-vibration plate KERN YPS-04 (400×450×60 mm, 30 kg)
YPS-05	Anti-vibration plate KERN YPS-05 (565×450×60 mm, 42 kg)

SOFTWARE

Model	Description
SCD-4.0-DL	Software SCD-4.0-DL (Scope of supplies: Download link for 1 license)
SCD-4.0-DLS05	Software SCD-4.0-DLS05 (Scope of supplies: Download link for 5 licenses)
SCD-4.0-PRO-DL	Software SCD-4.0-PRO-DL (Scope of supplies: Download link for 1 license)
SCD-4.0-PRO-DL-AS05	Software SCD-4.0-PRO-DL-AS05 (Scope of supplies: Download link for 5 licenses)

ENGLISH

SERVICES

Model	Description
961-248	Adjustment at the location of installation 961-248 (Not in combination with verification)
963-104	DAkkS calibration certificate 963-104
969-517	Confirmation of the manufacturer's specification (only in combination with DAkkS calibration certificate)969-517
970-108	Warranty extension (+2 years) 970-108

KERN Pictogram Overview

	External adjustment: Adjusting accuracy using external adjustment weight
	Data interface RS-232: For connection to printers, PCs or other peripheral devices for data transfer over longer distances. Network in bus topology possible
	GLP/ISO protocol: The measuring device generates a GLP-compliant printout
	Piece counting: Reference quantities selectable. Display can be switched from piece to weight
	Net total: The weight values of the recipe ingredients can be added up and the total weight of the recipe printed out
	Sum function: The weight values of weighed items can be added together and the total printed out
	Percentage determination: determining the deviation in % from the target value (100 %)
	Units can be switched to e.g. non-metric units
	Measuring with tolerance range (checkweighing): Upper and lower limit values can be programmed, e.g. for sorting, portioning or for measuring coatings or material thicknesses. The process is supported by an acoustic and/or optical signal
	Hold function: When the weighing conditions are unstable, a stable weight is calculated as an average value
	Suspended weighing: Load support with hook on the underside of the balance
	Universal plug-in power supply: With universal input and optional input socket adapters for EU, CH, GB or EU, CH, GB, US or EU, CH, GB, US, AUS
	Weighing principle single cell technology: Advanced version of the force compensation principle with the highest level of precision
	Package shipment by courier service: The duration of internal product provision is one day
	Accredited calibration (DKD): The duration of the accredited calibration is 3 working days