PROFESSIONAL MEASURING
SINCE 1844

KERN

Product brochure

30.10.2026

KERN PES 4200-2M

Robust laboratory and industrial precision scale for heavy items

ENGLISH



CONTACT

KERN & SOHN GmbH
Ziegelei 1
72336 Balingen
Germany

+49 7433 9933-0
info@kern-sohn.com
www.kern-sohn.com

FEATURES

- CAL adjustment program for adjusting precision, external test weights available separately (see test weights)
- Metal housing: robust and sturdy
- Weighing with tolerance range (checkweighing): Input of two upper and two lower limit values through four arrow keys. An audible and visual signal assists with the portioning, dispensing or grading
- Underfloor weighing: Possibility of load support with built-in loop on the underside of the balance
- Protective working cover included with delivery

TECHNICAL DATA

- Fluorescent display, bright with high contrast, digit height 14 mm
- Dimensions weighing surface W×D 200×200 mm, stainless steel
- Overall dimensions 220×333×93 mm
- Net weight approx. 4,4 kg
- Permissible ambient temperature 10 °C/30 °C

MAIN SCOPE OF APPLICATIONS

- Laboratory applications
- Industrial applications
- Research and development
- Time-based recording

PICTOGRAMS

Standard | Option | Factory



MODEL OVERVIEW

Model	Weighing capacity [Max]	Readability [d]	Reproducibility	Linearity	Dimensions weighing surface
PES 620-3M	620 g	0,001 g	0,001 g	± 0,003 g	140×120 mm
PES 2200-2M	2200 g	0,01 g	0,01 g	± 0,02 g	200×200 mm
PES 4200-2M	4200 g	0,01 g	0,01 g	± 0,02 g	200×200 mm
PES 6200-2M	6200 g	0,01 g	0,01 g	± 0,03 g	200×200 mm

Model	Weighing capacity [Max]	Readability [d]	Reproducibility	Linearity	Dimensions weighing surface
PES 15000-1M	15000 g	0,1 g	0,1 g	± 0,2 g	200×200 mm
PES 31000-1M	31000 g	0,1 g	0,1 g	± 0,4 g	250×220 mm

ACCESSORIES

Model	Description
474-926	RS232 interface cable 474-926
MLB-A05	RS232 interface cable MLB-A05
PES-A02	Relay output PES-A02
PES-A03	Device for suspended weighing PES-A03
PES-A04	Protective working cover PES-A04
PES-A04S05	Protective working cover PES-A04S05, scope of delivery: 5 items
YKC-01	Thermal printer YKC-01
YKG-01	Dot Matrix Printer YKG-01
YKH-01	Thermal printer YKH-01
YKI-10	RS232-Ethernet adapter YKI-10 (RS-232 standard, Ethernet, RS-485)
YKI-11	RS232-Ethernet adapter YKI-11 (Ethernet, RS-232 standard - 2x)
YKI-12	RS232-WiFi adapter YKI-12
YKT-01	Needle printer YKT-01
YPS-03	Antivibration table YPS-03
YPS-04	Anti-vibration plate KERN YPS-04 (400×450×60 mm, 30 kg)
YPS-05	Anti-vibration plate KERN YPS-05 (565×450×60 mm, 42 kg)

SOFTWARE

Model	Description
SCD-4.0-DL	Software SCD-4.0-DL (Scope of supplies: Download link for 1 license)
SCD-4.0-DLS05	Software SCD-4.0-DLS05 (Scope of supplies: Download link for 5 licenses)
SCD-4.0-PRO-DL	Software SCD-4.0-PRO-DL (Scope of supplies: Download link for 1 license)
SCD-4.0-PRO-DL-AS05	Software SCD-4.0-PRO-DL-AS05 (Scope of supplies: Download link for 5 licenses)

SERVICES

Model	Description
963-127	DAkkS calibration certificate 963-127
969-517	Confirmation of the manufacturer's specification (only in combination with DAkkS calibration certificate)969-517
970-106	Warranty extension (+2 years) 970-106

KERN Pictogram Overview

	External adjustment: Adjusting accuracy using external adjustment weight
	Data interface RS-232: For connection to printers, PCs or other peripheral devices for data transfer over longer distances. Network in bus topology possible
	Piece counting: Reference quantities selectable. Display can be switched from piece to weight
	Net total: The weight values of the recipe ingredients can be added up and the total weight of the recipe printed out
	Sum function: The weight values of weighed items can be added together and the total printed out
	Percentage determination: determining the deviation in % from the target value (100 %)
	Units can be switched to e.g. non-metric units
	Measuring with tolerance range (checkweighing): Upper and lower limit values can be programmed, e.g. for sorting, portioning or for measuring coatings or material thicknesses. The process is supported by an acoustic and/or optical signal
	Universal plug-in power supply: With universal input and optional input socket adapters for EU, CH, GB or EU, CH, GB, US or EU, CH, GB, US, AUS
	Weighing principle tuning fork: A resonating body is electromagnetically excited, causing it to oscillate
	Package shipment by courier service: The duration of internal product provision is one day
	Suspended weighing: Load support with hook on the underside of the balance
	Accredited calibration (DKD): The duration of the accredited calibration is 3 working days
	Control outputs (optocoupler, digital I/O): To connect relays, signal lamps, valves, etc.

ENGLISH