

# KERN RPB 3K3DM

Retail scale with memories for item prices



Display digit height	15 mm
Additional display	15 mm

## Construction

Dimension housing (W×D×H)	283×318×100,3 mm
Dimensions completely mounted (W×D×H)	283×318×110,3 mm
Dimensions weighing surface (W×D)	204×263 mm
Dimensions weighing surface	204×263 mm
Material housing	plastic
Material weighing plate	stainless steel
Level indicator	✓
Levelling feet adjustable	✓
Stand rotatable	no
Stand inclinable	no
Transport safety lock - bolt torque	0,1 Nm
Load cells - number	1

## Functions

Function for price calculation	✓
PLU - total	10
IP protection - complete device	-
Memory function	✓
Auto-off interval(s) in battery mode/rechargeable battery mode	off
Auto-off interval(s) in mains power mode	off
Tare function	manual (single)
Number of keys for operation	20

## Interface

Interfaces	RS-232 standard
------------	-----------------

## Power Supply

Supplied power supply	Power supply unit
Power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Plug-in power supply / adapter for countries - optional	EURO AUS UK US CH
Input voltage power supply / power [Max]	220 V - 240 V AC, 50 Hz
Power supply cable removable	removable

## Category

Brand	KERN
Product category	Industrial scale
Product group	Price computing scale
Product family	RPB

## Measuring System

Weighing system	Strain gauge
Number of weighing ranges	2
Weighing capacity [Max]	1500 g; 3000 g
Readability [d]	0,5 g; 1 g
Reproducibility	1 g; 2 g
Linearity	± 3 g; 6 g
Minimum weight [Min] (verifiable)	10 g
Resolution	3.000, 3.000
Tare range	-2999 g
Adjustment options	Adjusting with external weight
Recommended adjusting weight	3 kg (M1)
Stabilization time	1 s
Eccentric loading at 1/3 [Max]	5 g; 10 g
Conformity assessment possible	✓
Construction type of the scale	Multi-division balance
Units	g
Units (if device is conformity assessed)	g
Default unit	g
Loadcell type	Tscale BX6

## Display

Display type	LCD
Display backlight	✓

# KERN RPB 3K3DM

# KERN

Retail scale with memories for item prices

Input voltage device / power [Max]	12 V, 500 mA
Power socket for mains adapter	Hollow plug, inside plus, Ø outside 5,5 mm, Ø inside 2,1 mm, long 9,5 mm
Battery / accumulator type	Pb
Battery	no battery
Rechargeable battery	6 V, 3.2 Ah
Rechargeable battery operating time - backlight on	30 h
Rechargeable battery operating time - backlight off	60 h
Rechargeable battery charging time	12 h
Rechargeable battery optional	Rchrg. battery optional

## Environmental conditions

Ambient temperature [Min]	-10 °C
Ambient temperature [Max]	40 °C
Humidity of environment [Min]	0 %
Humidity of environment [Max]	80 %
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

## Approval

CE mark	✓
Conformity assessment possible ex works	✓
Accuracy classe	III
Verification scale interval [e]	0,5 g; 1 g

## Services (optional)

Article number for adjustment at the location of installation	961-247
Article number for conformity assessment	965-227
Article number for DAkkS calibration	963-127
Article number for certificate of conformity	969-517

## Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	510×342×196 mm
Shipping method	Parcel service
Net weight approx.	2,8 kg
Gross weight approx.	3,6 kg
Shipping weight	6,8 kg

Shipping volume weight	6,8 kg
------------------------	--------

## Product information

GTIN/EAN number	4045761252158
Trade number	84238125
REACH classification	no prohibited substances

## Pictograms

### STANDARD



### OPTION



### FACTORY

