

KERN MPC 250K100M

Compact personal floor scale – with approval for professional medical use in medical diagnostics, verification optional



Construction

Dimension display device (W×D×H)	200×130×60 mm
Dimensions weighing platform (W×D×H)	365×370×80 mm
Material housing	steel, lacquered
Material weighing plate	plastic
Material display housing	Plastics
Level indicator	✓
Wall mount	✓
Display device cable length	1,8 m

Functions

PreTare function	✓
Function for averaging under unstable weighing conditions	✓
Function for BMI calculation	✓
Hold function	✓
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min 5 min 30 min 15 min
Tare function	manual (single & multi)
Number of keys for operation	6

Interface

Interfaces	RS-232 (optional, factory)
------------	----------------------------

Power Supply

Supplied power supply	Power supply & battery function (battery not included)
Plug-in power supply type	Power adapter
Plug-in power supply / adapter for countries - included with the delivery	EURO UK CH
Plug-in power supply / adapter for countries - optional	EURO AUS UK US CH
Input voltage power supply / power [Max]	100 V - 240 V, 50 / 60 Hz
Input voltage device / power [Max]	12 V, 500 mA
Battery / accumulator type	Alkali(-Manganese)
Battery	6×1.5 V AA
Battery connection	Battery insert
Battery operating time	20 h
Rechargeable battery	MBC-A08

Category

Brand	KERN
Product category	Medical scale
Product group	Personal floor scale
Product family	MPC

Measuring System

Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	250 kg
Readability [d]	0,1 kg
Reproducibility	0,1 kg
Linearity	± 0,1 kg
Minimum weight [Min]	2 kg
Resolution	2.500
Tare range	249,9 kg
Adjustment options	Adjusting with external weight
Recommended adjusting weight	200 kg (M1)
Stabilization time	3 s
Warm-up time	10 min
Eccentric loading at 1/3 [Max]	0,1 kg
Default unit	kg
Units	kg
Conformity assessment possible	✓

Display

Display type	LCD
Display backlight	✓
Display digit height	25 mm
Languages of the user interface	Symbol language

KERN MPC 250K100M

KERN

Compact personal floor scale – with approval for professional medical use in medical diagnostics, verification optional

Rechargeable battery operating time - backlight on	20 h
Rechargeable battery operating time - backlight off	40 h
Rechargeable battery charging time	12 h
Rechargeable battery optional	Rchrg. battery optional - intern

Environmental conditions

Ambient temperature [Min]	-10 °C
Ambient temperature [Max]	40 °C
Humidity of environment [Max]	80 %
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

Approval

CE mark	✓
Conformity assessment possible ex works	✓
Accuracy classe	III
Verification scale interval [e]	0,1 kg

Services (optional)

Article number for adjustment at the location of installation	961-249
Article number for conformity assessment	965-129
Article number for DAkkS calibration	963-129
Article number for certificate of conformity (verification)	969-517

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	560×440×200 mm
Net weight	8,4 kg
Shipping method	Parcel service
Net weight approx.	9 kg
Gross weight approx.	11 kg
Shipping weight	10,02 kg

Pictograms

STANDARD



OPTION



FACTORY

