

KERN OBN 148

The fluorescence microscope for the professional user



Ocular	
Ocular type	Eyepiece HWF 10 x / Ø 20mm with anti-fungus, high eye point
Ocular field width	HWF
Ocular magnifications	10 x
Ocular visual field	20 mm
Ocular diameter	23,2 mm

Objective	
Objectives - Details	Objective Infinity Plan 10 x / 0,25 anti-fungus
	Objective Infinity Plan 100 x / 1,25 oil, spring, anti-fungus
	Objective Infinity Plan 20 x / 0,4 spring, anti-fungus
	Objective Infinity Plan 4 x / 0,11 anti-fungus
	Objective Infinity Plan 40 x / 0,66 spring, anti-fungus
Objectives magnifications	4 x / 10 x / 20 x / 40 x / 100 x

Illumination	
Illuminance	Reflected light Transmitted light
Illumination type incident light	HBO
Illumination type transmitted light	Halogen
Illumination intensity incident light	100 W
Illumination intensity transmitted light	20 W
Illumination dimmable	Transmitted light
Koehler illumination	✓
Filter possible	✓
Aperture diaphragm	✓
Field diaphragm	✓
Brand of light bulb	Philips

Focussing	
Field of view [Min]	0,2 mm
Field of view [Max]	5 mm
Torque regulation	✓
Fine drive minimum	0,002 mm
Focussing mechanism	coaxial coarse and fine drive

Category

Brand	Optics
Product category	Microscope
Product group	Fluorescence microscope
Product family	OBN-14

Construction

Dimension (WxDxH)	530x220x490 mm
Optical system	Infinity
Tube type	Trinocular
Tube angle of inclination	30°
Tube 360° rotation	✓
Tube type	Siedentopf
Light distribution	100:0

Contrasting methods	Bright field
	Darkfield (optional)
	Fluorescent
	Polarisation (optional)
	Phase contrast (optional)

Standard objectives	4x
	10x
	20x
	40x
	100x

Lens quality	Infinity Plan
Nosepiece screw-in locations	5
Interpupillary distance [Min]	50 mm
Interpupillary distance [Max]	75 mm
Diopter adjustment	both-sided
Diopter adjustment [Min]	-5
Diopter adjustment [Max]	5

KERN OBN 148



The fluorescence microscope for the professional user

Power Supply

Supplied power supply	Power supply unit
Plug-in power supply type	Built-in power supply
Plug-in power supply / adapter for countries - included with the delivery	EURO
	AUS
Plug-in power supply / adapter for countries - optional	UK
	US
	CH
Input voltage power supply / power [Max]	100 - 240 V
Input voltage device / power [Max]	100 - 240 V

Environmental conditions

Storage temperature [Min]	-5 °C
Storage temperature [Max]	40 °C

Approval

CE mark	✓
---------	---

Packing & Shipping

Delivery time	1 d
Dimensions packaging (W×D×H)	500×440×500 mm
Net weight	15,978 kg
Shipping method	Parcel service
Net weight approx.	16 kg
Gross weight approx.	24 kg
Shipping weight	23 kg

Pictograms

STANDARD



OPTION

