

COATING THICKNESS MEASUREMENT

PROFESSIONAL MEASURING



2018

KERN Pictograms



Adjusting program (CAL):
For quick setting of the instrument's accuracy. External adjusting weight required.



Calibration block:
standard for adjusting or correcting the measuring device.



Peak hold function:
capturing a peak value within a measuring process.



Scan mode:
continuous capture and display of measurements.



Push and Pull:
the measuring device can capture tension and compression forces.



Length measurement:
captures the geometric dimensions of a test object or the movement during a test process.



Focus function:
increases the measuring accuracy of a device within a defined measuring range.



Internal memory:
to save measurements in the device memory.



Data interface RS-232:
bidirectional, for connection of printer and PC.



Data interface USB:
To connect the measuring instrument to a printer, PC or other peripheral devices.



Data interface Infrared:
To transfer data from the measuring instrument to a printer, PC or other peripheral devices.



Control outputs (optocoupler, digital I/O):
to connect relays, signal lamps, valves, etc.



Analogue interface:
to connect a suitable peripheral device for analogue processing of the measurements



Statistics:
using the saved values, the device calculates statistical data, such as average value, standard deviation etc.



PC Software:
to transfer the measurement data from the device to a PC.



Printer:
a printer can be connected to the device to print out the measurement data.



GLP/ISO record keeping:
of measurement data with date, time and serial number. Only with SAUTER printers



Measuring units:
Weighing units can be switched to e.g. non-metric at the touch of a key. Please refer to website for more details.



Measuring with tolerance range (limit-setting function):
Upper and lower limiting can be programmed individually. The process is supported by an audible or visual signal, see the relevant model



ZERO:
Resets the display to "0".



Battery operation:
Ready for battery operation. The battery type is specified for each device.



Rechargeable battery pack:
rechargeable set.



Mains adapter:
230V/50Hz in standard version for EU. On request GB, AUS or USA version available.



Power supply:
Integrated, 230V/50Hz in EU. More standards e.g. GB, AUS or USA on request.



Motorised drive:
The mechanical movement is carried out by an electric motor.



Motorised drive:
The mechanical movement is carried out by a synchronous motor (stepper).



Fast-Move:
the total length of travel can be covered by a single lever movement.



DAkKS calibration possible:
The time required for DAkKS calibration is shown in days in the pictogram.



Factory calibration:
The time required for factory calibration is specified in the pictogram.



Package shipment:
The time required for internal shipping preparations is shown in days in the pictogram.



Pallet shipment:
The time required for internal shipping preparations is shown in days in the pictogram.

Sales conditions



All prices are valid as of January 1st 2018 until a new version of the SAUTER catalogue is released. In Europe, all prices do not include the applicable V.A.T.

At SAUTER there is no minimum order value. For orders less than € 15.00 there is no re-sale discount available.

Delivery Conditions: we supply ex works Balingen, i.e. the transport costs are invoiced. Any goods supplied, remain SAUTER's property until Measuring in a tolerance area (limit value function). Upper and lower limit value is programmable. The measurement process is supported by an acoustic and visual signal, see respective models complete payment for the goods sold has been received.



Delivery is usually via courier service.



When you see this symbol by truck, please ask for prices.

Extract from general terms and conditions:

Court of jurisdiction/Legal domicile: 72336 Balingen, Germany;
Commercial register N°: HRB 400865, AG Stuttgart;
Managing director: Albert Sauter, Martin Sauter.
For the full Terms and Conditions, please refer to the website.
www.kern-sohn.com/en/kern/agbs.html

Price changes and product changes are likely in individual cases due to product modifications as well as error.

Sale or return: within 14 days of purchase. Not valid for order-specific adaptations such as special productions, cable extensions, special weights, etc. or test services such as calibration etc. Depending on the time and effort involved, there may be processing and storage costs, please ask for details.

Warranty: 2 years. (Does not apply to consumables such as batteries, rechargeable battery packs, etc.)

After-Sales-Service



Repair services within 1 week at our plant in Balingen, transportation costs are additional. Our expert Service technicians will be pleased to assist you and will make sure that your device is quickly back in operation.

Price reduction on a new device: if repair costs are exceeding the current value of the defective device, a new device will be offered at a discount price. This offer is valid only up to 2 years after warranty expiration.

Spare parts service within 48 hours, transportation costs are additional.

Visit us our online shop: www.sauter.eu

Online-Shop

At your disposal round the clock. Delivery and service via your specialist dealer.

Measuring instruments Quick-Finde

Find the product you want with the "Measuring instruments Quick-Finder" in no time.

Calibration

In our accredited DAkks calibration laboratories, we produce internationally recognised DAkks and Factory calibration certificates for balances and test weights as well as measuring instruments.



Services



KERN DirectCash: The quick, secure COD procedure for protection against non-payment. With the KERN DirectCash COD system, you can safely deliver orders to end customers with unknown credit rating, with no risk of non-payment. Please request further details on this procedure.

Hire Purchase

Financing is available using KERN hire purchase – easy and convenient.

Hire Purchase gives you the option of purchasing any product from the range against a simple monthly installment. The product value is financed over the period of the agreement. On payment of the last installment, the ownership of the contract item automatically transfers from the contractor to the contractee.

The Hire Purchase Agreement can – if you so choose – be set for a period of between one and five years. This package includes the transfer of items as well as the guarantee for the entire transfer period.

Compared with buying the product, KERN hire purchase offers the advantage that the initial financial investment is largely not applicable. This is particularly relevant when purchasing a number of products, for example when refitting a laboratory, a company department or a hospital ward. In addition the monthly installments constitute a direct cost and the item does not have to be capitalised by the purchaser. Do you have queries to our hire purchase? Our customer consultants are glad to help you.

Marketing support



Catalogues, brochures, branch prospectuses – your own personalised marketing tools

Our catalogue and branch prospectuses are available free of charge. A neutral version of the catalogue, without the SAUTER address imprint, is also available for your marketing activities free of charge, larger quantities on request..

On demand we will print your company address on address labels free of charge, for the backside of the catalogue, larger quantities on request. In this way you will receive your individual marketing tool.

Our catalogues and branch prospectuses are available in following languages: DE, GB, FR, IT, ES

Special offers

Special offers, special models and opportunities – something for everybody and always up to date – just drop in!

One-Stop-Shopping

From force gauge to test stand – everything from one supplier.

Downloads


For each model there is an individual brochure, user manual or pictures.




Coating thickness measurement

Measurement of coating thicknesses is known from, for example, the paint measurement for coating thickness at cars. In fact, these measurements are used much more widely in industrial applications. This is where the thickness of the surface finish is measured, such as galvanisation, zinc coating etc, or also lacquers.


Fundamentally there are two measuring principles for determining coating thickness:


 **Typ F:** Non-magnetic coatings on magnetic metals, such as iron or steel (magnetic induction principle). Here are some sample material combinations:

- 1) [aluminium, chrome, copper, rubber, lacquer] on
- 2) [steel, iron, alloys, magnetic s tainless steel]

 **Typ N:** Insulating coatings on non-magnetic metals, such as aluminium (eddy current principle). Here are some sample material combinations:

- 3) [lacquer, paints, enamel, chrome, plastics] on
- 4) [aluminium, brass, sheet metal, copper, zinc, bronze]

 **Typ FN:** All coatings as for type F and N on all metals as for type F and N (combination of magnetic induction and eddy current principle)



Taras Mikitisin
Product specialist
Coating thickness measurement

Tel. +49 [0] 7433 9933- 143
Fax +49 [0] 7433 9933-29143
mikitisin@kern-sohn.com

Quick-Finder

Readout [d] µm	Measuring range [Max] µm	Model SAUTER	Price excl. VAT, ex works €	Page
0,1 1	100 1000	TB 1000-0.1F.	320,-	38
0,1 1	100 1000	TB 1000-0.1N.	360,-	38
0,1 1	100 1000	TB 1000-0.1FN.	400,-	38
0,1 1	100 1250	TC 1250-0.1F.	360,-	39
0,1 1	100 1250	TC 1250-0.1N.	400,-	39
0,1 1	100 1250	TC 1250-0.1FN.	460,-	39
0,1 1	100 1250	TC 1250-0.1FN-CAR.	470,-	39
0,1 1	100 1250	TE 1250-0.1F.	360,-	40
0,1 1	100 1250	TE 1250-0.1N.	400,-	40
0,1 1	100 1250	TE 1250-0.1FN.	460,-	40
0,1 1	100 1250	TF 1250-0.1FN.	530,-	41
0,1 1	100 1250	TG 1250-0.1FN.	530,-	41
0,1 1	100 2000	TB 2000-0.1F.	290,-	38



04

Your reliable worktool for every day: light, easy, precise

Features

- **External sensor** for difficult-to-access measuring points
- **Base plate and calibration foils** included
- **1 Delivered in a robust carrying case**
- **Offset-Accur:** This function allows you to adjust the instrument precisely on the locally measured range by a two-point calibration. This results in a superior accuracy of approx. 1 % of the measured value
- **Selectable measuring units:** mm, µm, mil
- **Auto-Power-Off**
- SAUTER TB 2000-0.1F: Specifically designed for the automobile industry, Precision: Standard 5 % of measured value

Technical data

- Precision:
 - Standard: 3 % of measured value
 - Offset-Accur: 1 % of measured value
- Minimal measuring area: 6 mm
- Smallest sample surface (radius)
 - Type F:
 - Convex: 1,5 mm
 - Concave: 25 mm
 - Type N:
 - Convex: 3 mm
 - Concave: 50 mm
- Minimal base thickness: 0,3 mm
- Dimensions W×D×H 69×32×161 mm
- Battery operation, batteries standard 4× 1.5V AA
- Net weight approx. 0,26 kg

Accessories

- **2 Calibration foils** for increased measuring accuracy (covers the range from 20 up to 2000 µm, with < 3 % tolerance), sim. to illustration, SAUTER ATB-US07, **€ 105,-**
- **3 External sensor**, Type F, SAUTER ATE 01, **€ 105,-**
- **4 External sensor**, Type N, SAUTER ATE 02, **€ 110,-**

STANDARD

CAL BLOCK FOCUS ZERO BATT 1 DAY

OPTION

ISO +4 DAYS

Model	Measuring range [Max] µm	Readout [d] µm	Test object	Price excl. of VAT ex works €	Option Factory calibration certificates	
					KERN	€
SAUTER TB 1000-0.1F.	100 1000	0,1 1	Non-magnetic coatings on iron, steel (F)	320,-	961-110	120,-
TB 2000-0.1F.	100 2000	0,1 1	Non-magnetic coatings on iron, steel (F)	290,-	961-110	120,-
TB 1000-0.1N.	100 1000	0,1 1	Insulating coatings on non-magnetic metals (N)	360,-	961-110	120,-
TB 1000-0.1FN.	100 1000	0,1 1	Combination instrument: F/N	400,-	961-112	170,-



Your constant companion – compact and easy to use

Features

- Ergonomic design for easy handling
- **Data interface RS-232**, included
- **Base plate and calibration foils** included
- **Delivered in a robust carrying case**
- **Offset-Accur:** This function allows you to adjust the instrument precisely on the locally measured range by a two-point calibration. This results in a superior accuracy of approx. 1 % of the measured value
- **Selectable measuring units:** μm , mil

2 SAUTER TC 1250-0.1FN-CAR:

- Specifically designed for the automobile industry
- **Automatic recognition of measuring mode** (F or N): “point and shoot”
- **Simple and convenient 1-key operation**


Technical data

- Precision:
 - Standard: 3 % of measured value or $\pm 2,5 \mu\text{m}$
 - Offset-Accur: 1 % of measured value or $\pm 1 \mu\text{m}$
- Smallest sample surface (radius)
 - Type F:
 - Convex: 1,5 mm
 - Concave: 25 mm
 - Type N:
 - Convex: 3 mm
 - Concave: 50 mm
- Minimal base thickness: 0,3 mm
- Dimensions WxDxH 65x28x131 mm
- Battery operation, batteries standard 4x 1.5V AAA
- Net weight approx. 81 g

Accessories

- **Software**, interface cable included, SAUTER ATC-01, **€ 90,-**
- **Calibration foils** for increased measuring accuracy (covers the range from 20 up to 2000 μm , with < 3 % tolerance), SAUTER ATB-US07, **€ 105,-**

STANDARD



OPTION



Model	Measuring range [Max] μm	Readout [d] μm	Test object	Price excl. of VAT ex works €	Option Factory calibration certificates	
					KERN	€
SAUTER TC 1250-0.1F.	100 1250	0,1 1	Non-magnetic coatings on iron, steel (F)	360,-	961-110	120,-
TC 1250-0.1N.	100 1250	0,1 1	Insulating coatings on non-magnetic metals (N)	400,-	961-110	120,-
TC 1250-0.1FN.	100 1250	0,1 1	Combination instrument: F/N	460,-	961-112	170,-
TC 1250-0.1FN-CAR.	100 1250	0,1 1	Combination instrument: F/N	470,-	961-112	170,-



Ergonomic design and external sensor for highest ease of use

Features

- **External sensor** for difficult-to-access measurements
- **Data interface RS-232**, included
- **Base plate and calibration foils** included
- **1 Delivered in a robust carrying case**
- **Offset-Accur:** This function allows you to adjust the instrument precisely on the locally measured range by a two-point calibration. This results in a superior accuracy of approx. 1 % of the measured value
- **Selectable measuring units:** µm, mil
- **Auto-Power-Off**

Technical data

- Precision:
 - Standard: 3 % of measured value or ± 2,5 µm
 - Offset-Accur: 1 % of measured value or ± 1 µm
- Smallest sample surface (radius)
 - Type F:
 - Convex: 1,5 mm
 - Concave: 25 mm
 - Type N:
 - Convex: 3 mm
 - Concave: 50 mm
- Minimal base thickness: 0,3 mm
- Dimensions W×D×H 65×28×131 mm
- Battery operation, batteries standard 4× 1.5V AAA
- Net weight approx. 81 g

Accessories

- **Data transfer software**, interface cable included, SAUTER ATC-01, **€ 90,-**
- **Calibration foils** for increased measuring accuracy (covers the range from 20 up to 2000 µm, with < 3 % tolerance), SAUTER ATB-US07, **€ 105,-**
- **2 External sensor**, TypeF, SAUTER ATE 01, **€ 105,-**
- **3 External sensor**, TypeN, SAUTER ATE 02, **€ 110,-**

STANDARD

OPTION

Model	Measuring range [Max] µm	Readout [d] µm	Test object	Price excl. of VAT ex works €	Option Factory calibration certificates	
					KERN	€
SAUTER TE 1250-0.1F.	100 1250	0,1 1	Non-magnetic coatings on iron, steel (F)	360,-	961-110	120,-
TE 1250-0.1N.	100 1250	0,1 1	Insulating coatings on non-magnetic metals (N)	400,-	961-110	120,-
TE 1250-0.1FN.	100 1250	0,1 1	Combination instrument: F/N	460,-	961-112	170,-

PREMIUM
★★★

PREMIUM
★★★



SAUTER TF

SAUTER TG

Premium measuring devices for paint coating, lacquer coating etc.

Features

- **1** LCD display, backlit, display of all information at a glance
- **Offset-Accur:** This function allows you to adjust the instrument precisely on the locally measured range by a two-point calibration. This results in a superior accuracy of approx. 1 % of the measured value
- **Scan mode** for continuous measurement or single point measuring mode
- **Mini Statistics Kit:** displays the measured result, the average value and the max and the min value
- **Internal memory** up to 99 values
- **Selectable measuring units:** μm, mil
- **Base plate and calibration foils** included
- **Data interface RS-232** standard
- **2** Delivered in a robust carrying case, figure shows SAUTER TF

Technical data

- Precision:
 - Standard: 3 % of measured value or ± 2,5 μm
 - Offset-Accur: 1 % of measured value or ± 1 μm
- Minimal base thickness: 0,3 mm
- Dimensions W×D×H 65×35×126 mm
- Battery operation, batteries standard 2× 1.5V AAA
- Net weight approx. 81 g


Accessories

- **Software**, interface cable included, SAUTER ATC-01, **€ 90,-**
- **Calibration foils** for increased measuring accuracy (covers the range from 20 up to 2000 μm, with < 3 % tolerance), SAUTER ATB-US07, **€ 105,-**
- SAUTER TG: **External sensor**, TypeFN, SAUTER ATG 01, **€ 130,-**

SAUTER TG:

- **External sensor** for difficult-to-access measuring points

STANDARD



OPTION



Model	Measuring range [Max] μm	Readout [d] μm	Test object	Smallest sample surface (radius) mm	Price excl. of VAT ex works €	Option Factory calibration certificates	
						KERN	€
SAUTER TF 1250-0.1FN.	100 1250	0,1 1	Combination instrument: F/N	F: Convex: 1,5 Concave: 25	530,-	961-112	170,-
SAUTER TG 1250-0.1FN.	100 1250	0,1 1	Combination instrument: F/N	N: Convex: 3 Concave: 50	530,-	961-112	170,-

fast

- 24 hours delivery service – order today, on its way tomorrow
- Sales & service hotline from 8:00 am to 6:00 pm

reliable

- 2 years warranty

diverse

- One-stop-shopping: from force gauges up to light measuring instruments – everything from one supplier
- Quick as a flash, find the product you want with the “Measuring instruments Quick-Finder” at www.sauter.eu



Our team of consultants will assist you

from Monday to Friday
from 8:00 am to 6:00 pm



www.sauter.eu

Information on current product availability, product data sheets, user instructions, useful knowledge, technical glossary, images and much for you to download, practical topic areas, which will guide you to the right product in your industry as well as a smart search engine for measuring instruments

SAUTER service guarantee

“We at SAUTER are only satisfied when we’ve found the very best solution for you. After all, our heritage from the Swabian Jura Mountains and the famous inventive talent of the people that live here, means we have an exceptional reputation to maintain.”

Printed in Germany
by SAUTER GmbH
z-cs-gb-sp-20181

Do you have questions about our products?
Our customer consultants will be pleased to assist you:

Product specialist Measuring technology



Irmgard Russo

Tel. +49 [0] 7433 9933-208
Fax +49 [0] 7433 9933-29208
russo@kern-sohn.com

UK, IE, MT, Scandinavia



Marietta Diener

Tel. +49 [0] 7433 9933-167
Fax +49 [0] 7433 9933-29167
Mobil +49 [0] 151 46143236
diener@kern-sohn.com

DK, DE (zip code 0, 1, 2)



Bettina Schwedt

Tel. +49 [0] 7433 9933-141
Fax +49 [0] 7433 9933-29141
Mobil +49 [0] 171 3059661
bettina.schwedt@kern-sohn.com

ES, PT, Central and South America, EE, LT, LV, PL



Jesús Martínez

Tel. +49 [0] 7433 9933-209
Fax +49 [0] 7433 9933-29209
Mobil +49 [0] 151 46143229
jesus.martinez@kern-sohn.com

BG, South East Asia, AUS, NZ, North America, Middle East, Africa, Oceania, DE (zip code 3)



Corinna Klaass

Tel. +49 [0] 7433 9933-215
Fax +49 [0] 7433 9933-29215
klaass@kern-sohn.com

NL, SLO, HR, BA, RS, MK, Germany (zip code 4)



Taras Mikitisin

Tel. +49 [0] 7433 9933-143
Fax +49 [0] 7433 9933-29143
Mobil +49 [0] 171 5590115
mikitisin@kern-sohn.com

HU, RO Germany zip code 5, 6)



Fabienne Kolbus

Tel. +49 [0] 7433 9933-305
Fax +49 [0] 7433 9933-29305
fabienne.kolbus@kern-sohn.com

GUS, CZ, SK



Inna Wandler

Tel. +49 [0] 7433 9933-167
Fax +49 [0] 7433 9933-29167
wandler@kern-sohn.com

Technical Service



Stefan Rothmund

Tel. +49 [0] 7433 9933-179
Fax +49 [0] 7433 9933-195
rothmund@kern-sohn.com

DAkKS Calibration Service



FR, BeNeLux, DK, GR, TR, North,
Maghreb, Africa, Central & South
America, Germany (Zip Code 8, 9)

Athina Ioakimidou

Tel. +49 [0] 7433 9933-123
Fax +49 [0] 7433 9933-29123
athina.ioakimidou@kern-sohn.com



Sauter GmbH
c/o KERN & SOHN GmbH
Ziegelei 1
72336 Balingen
Germany

Tel. +49 [0] 7433 9933-0
Fax +49 [0] 7433 9933-149
info@sauter.eu
www.sauter.eu